

ZONE WORKSHEET

Project Name: _____

Contractor Name: _____

Project Location: _____

Contractor Address: _____

Design Temp: (Indoor) _____ (Outdoor) _____

Zone Name: _____

Tube Options: Onix: _____ RadiantPex+: _____ RadiantPex-AL: _____

3/8" _____ 1/2" _____ 5/8" _____ 3/4" _____ 1" _____

Applications: _____ Staple-Up: Subfloor Thickness = _____ Joist Spacing = _____ Plates: Aluminum or FlexPlate

_____ Slab (Thickness = _____) _____ Thin Slab (Thickness = _____)

Room Name				
Manifold Type (Copper, Stainless Steel)				
Floor Covering				
Room Length				
Room Width				
Area/Perimeter				
Unheated Area				
Ceiling R Value				
Skylight Area				
Fireplace (QTY)				
Exhaust Fans (QTY)				
recessed Lights (QTY)				
Space Below (Heated, unheated)				
Under Floor Insulation R-Value				
Banded Area				

NOTES

FOR SLABS:

- Insulation assumed 4' deep, 1" thick along perimeter in vertical plane.
- Horizontal Insulation thickness ____"; Area ____'.

PLEASE NOTE:

- Unheated area refers to floor under permanent objects such as cabinets or bath fixtures, and will be subtracted from effective radiant panel area.
- Door area is entered separately from windows.
- Space below is conditioned or unconditioned space (crawl space, etc.).
- Unless noted, recessed lights assumed to be sealed type.
- Banded area refers to high-intensity heated areas such as before a slider or large glass area.
- Underfloor insulation R-19 minimum.