



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337
 States

Quotation:
Q-2980-S-1

To:	Contractor Holder Ohio Cincinnati, Ohio	Bid Date:	2018-07-18
Attn.:	N/A	Expiry Date:	2018-08-17
Phone:	800-542-1682	Creator:	Dave Evans , davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Todd Schneider , todds@disney-mclane.com
		Shipping Address:	1973 Edison Dr, Piqua, Ohio, United States

Job Name: Edison State CC Robinson Student Career Ctr Piqua,OH

Architect: SHP Leading Design (Steed Hammond Paul)

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
L-1	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
Note: P000 - 22-Lavatory Schedule			
WC-1	ISCA-101-L/R Watts - single, horizontal, cast iron fitting, left/right side outlet	\$1,587.50	1
	ISCA-101-D Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support	\$2,967.00	1
	ISCA-121 Watts - single, vertical, cast iron fitting	\$1,801.00	1
	ISCA-121-D Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts	\$3,181.50	1
	ISCA-131-L/R Watts - single, vertical, cast iron fitting, left/right side outlet	\$2,105.50	1
	ISCA-131-D Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support	\$3,480.00	1

Note: P000 - 22-Water Closet Schedule

EWC-1	CA-431-1		\$1,215.00	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.			
Note: P000 - 22-Electric Water Cooler and Drinking Fountain Schedule				
RD-1	RD-303-D-F-K		\$1,818.00	1
	Watts - epoxy coated, 16-5/8" (422 mm) diameter, cast iron body, flashing clamp and integral gravel stop, no-hub outlet, self locking, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, adjustable extension flange, 3"Ø (76 mm) outlet size			
Note: P000 - 22-Drainage Fixture Schedule & Spec 22 14 23-1; Equal to Zurn Z100.				
RD-2	RD-303-D-F-K-W		\$2,240.00	1
	Watts - 16-5/8" (422 mm) diameter, cast iron body, flashing clamp and integral 4" (102 mm) high internal stand pipe, no-hub outlet, 15-1/4" (387 mm) diameter, ductile iron dome, underdeck clamp, adjustable extension flange, 3"Ø (76 mm), 4"Ø (102 mm) outlet sizes			
Note: P000 - 22-Drainage Fixture Schedule & Spec 22 14 23-1; Equal to Zurn Z100.				
WHA (bellows type)	SS Series			1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)			
	SS-A		\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection			
	SS-B		\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection			
	SS-C		\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection			
	SS-D		\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection			
	SS-E		\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection			
	SS-F		\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection			
Note: P000 - Detail 3 & Spec 22 11 19-2; Equal to JR Smith 5000 Series				
WHA (piston type)	LF15M2-DR Series			1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)			
	LF15M2-A-DR		\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection			
	LF15M2-B-DR		\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection			
	LF15M2-C-DR		\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection			
	LF15M2-D-DR		\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection			
	LF15M2-E-DR		\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection			
	LF15M2-F-DR		\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection			
Note: Spec 22 11 19-2				
DSN	RD-950			1
	Watts - round, fabricated type 304 stainless steel, securing flange and secured perforated hinged strainer, no hub			

	RD-950,3,4 Watts - 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$2,910.00	1
	RD-950,6 Watts - 6"Ø (152 mm)	\$3,074.00	1
	RD-950,8 Watts - 8"Ø (203 mm)	\$3,220.00	1
	RD-950,10 Watts - 10"Ø (254 mm)		1
	RD-950,12 Watts - 12"Ø (305 mm)		1
Note: Spec 22 14 23-2; Equal to Zurn Z199-DC			
WCO	CO-460-RD Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		1
	CO-460-RD,2 Watts - 2"Ø (51 mm)	\$364.00	1
	CO-460-RD,3 Watts - 3"Ø (76 mm)	\$417.50	1
	CO-460-RD,4 Watts - 4"Ø (102 mm)	\$611.50	1

Note: Spec 22 14 23-2

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
Point of Use Mixing Valve (TMV-5)	LFE480-11 Powers - 3/8 LFE480-11	\$332.00	1

Note: Spec 22 11 19-2 & Spec 22 40 00-3

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

Terms

Above prices are net.
 All taxes are extra.
 Partial or expedited shipments, at customer request, may result in additional freight charges.
 Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.
 Please ensure that all quoted product meets your projects specifications.
 Our company will only be responsible for products shown on the attached quotation.