



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337
 States

Quotation:
Q-2427-S-1

To:	Contractor Holder Indiana Cincinnati, Ohio	Bid Date:	2018-11-07
Attn.:	N/A	Expiry Date:	2018-12-07
Phone:	800-542-1682	Creator:	Dave Evans, davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Rick Bayne, rickb@disney-mclane.com
		Shipping Address:	25802 SR 19, Arcadia, Indiana, United States

Job Name: Hamilton Heights High School Renovations

Engineer: Heapy Engineering **Architect:** krM Architecture

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
PF-D	HY-420 Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, seat casting and internal working parts, wall mount, bronze wall casing, chrome plated face, integral vacuum breaker		1
	HY-420,-4,-6,-8 Watts - 4" (102 mm), 6" (152 mm), 8" (203 mm) thick	\$864.50	1
	HY-420,-10,-12,-14 Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick	\$1,006.00	1
	HY-420,-16,-18 Watts - 16" (406 mm), 18" (457 mm) thick	\$1,146.50	1
	HY-420,-20,-22,-24 Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick	\$1,188.00	1
	Note: Dwg AP1-2 Plumbing Fixture Schedule & Spec 22 11 19 - 1; Equal to Zurn Z1321		
FD/FD-1	FD-100-A5-7 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer, trap primer connection		1
	FD-100-A5-7,2,3,4 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$481.00	1
	FD-100-A5-7,6 Watts - 6"Ø (152 mm)	\$601.50	1
	Note: Dwg AP1-2 Plumbing Fixture Schedule; Equal to Smith 2010		
FD	LFTP300-DR Series Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		1
	LFTP300T Watts - 1/2", Threaded Inlet and Outlet Connect	\$270.00	1
	LFTP300S ATS - 1/2", Solder Inlet and Threaded Outlet Connect	\$270.00	1
	LFTP300-DU-DR Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit	\$189.00	1

Note: Dwg AP1-2 Plumbing Fixture Schedule & Spec 22 11 19 - 2;

A1/A2	ISCA-102-L/R	\$4,641.00	1
	Watts - horizontal, cast iron fitting, 4"Ø, no hub waste connection, left/right side outlet, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, epoxy coated, ductile iron, foot support		
	ISCA-102-D	\$8,950.00	1
	Watts - double, horizontal, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, epoxy coated, ductile iron, foot support		
	ISCA-122	\$5,108.00	1
	Watts - single, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, , 2"Ø, no hub vent connection. epoxy coated ductile iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, ductile iron foot support		
	ISCA-122-D	\$9,847.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, , 2"Ø, no hub vent connection. epoxy coated ductile iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, ductile iron foot support		
	ISCA-132-L/R	\$5,413.50	1
	Watts - single, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection and 4" Ø no hub side inlets, left/right side outlet, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, ductile iron foot support		
	ISCA-132-D	\$10,146.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection and 4" Ø no hub side inlets, , 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, ductile iron foot support		
	Note: Dwg P6-0 Plumbing Fixtures Schedule & Spec 22 13 19 - 1;		
B3/B4	TCA-411 Series		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411	\$989.50	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	TCA-411-D	\$1,411.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	Note: Dwg P6-0 Plumbing Fixtures Schedule;		
C1/C2	CA-321	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
	Note: Dwg P6-0 Plumbing Fixtures Schedule;		
G1/G2	CA-431-1	\$1,215.00	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
	Note: Dwg P6-0 Plumbing Fixtures Schedule;		

FD1	FD-100-A5-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer, trap primer connection		
	FD-100-A5-7,2,3,4	\$481.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-A5-7,6	\$601.50	1
	Watts - 6"Ø (152 mm)		
Note: Dwg P6-0 Drains Schedule; Equal to Smith 2005			
FD2	FD-100-ER9		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 9" (229 mm) diameter, nickel bronze, extended rim strainer		
	FD-100-ER9,2,3,4	\$1,566.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-ER9,6	\$1,685.00	1
	Watts - 6"Ø (152 mm)		
Note: Dwg P6-0 Drains Schedule; Equal to Smith 2005-F38			
FD3	FS-710-FC-1-5-150		1
	Watts - cast iron body, 6-1/4" (159 mm) deep, no-hub outlet, aluminum dome bottom strainer, 7-11/16" (195 mm) square, nickel bronze top, sediment bucket, flange w/weepholes and flashing clamp, 1/2 Grate		
	FS-710-FC-1-5-150,2,3,4	\$2,596.00	1
	Watts - 2" (51mm), 3" (76mm), 4" (102mm)		
Note: Dwg P6-0 Drains Schedule; Equal to Smith 3101			
OD1/OD2	RD-300-D-F-K81-W		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, rough bronze dome, underdeck clamp, adjustable extension flange, 4" Internal Water Dam		
	RD-300-D-F-K81-W,2,3,4	\$2,858.50	1
	Watts - 2" (51 mm), 3" (76 mm), 4" (102 mm)		
	RD-300-D-F-K81-W,5,6	\$3,161.00	1
	Watts - 5" (127 mm), 6" (152 mm)		
	RD-300-D-F-K81-W,8,10	\$3,463.50	1
	Watts - 8" (203 mm), 10" (254 mm)		
Note: Dwg P6-0 Drains Schedule; Equal to Smith 1074			
RD1/RD2	RD-300-D-F-K81		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, rough bronze dome, underdeck clamp, adjustable extension flange		
	RD-300-D-F-K81,2,3,4	\$2,435.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-300-D-F-K81,5,6	\$2,738.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	RD-300-D-F-K81,8,10	\$3,040.50	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
Note: Dwg P6-0 Drains Schedule; Equal to Smith 1015			
Water Hammer Arrestor Bellows	SS Series		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		

	SS-B	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: Spec 22 11 19 - 2			
Water Hammer Arrestor Piston	LF15M2-DR Series		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: Spec 22 11 19 - 2			
CO Floor	CO-200-R		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200-R,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-R,3	\$661.00	1
	Watts - 3"Ø (76 mm)		
	CO-200-R,4	\$881.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 13 19 - 1; equal to Smith 4020			
CARPET CLAMPING FLANGE (-CF) = \$285.00 LIST ADDER			
CARPET MARKER (-RC) = \$78.00 LIST ADDER			
NB HEAVY DUTY (-RX) = \$155.00 LIST ADDER			
TILE RECESS (-T) = NO ADDITIONAL			
TERRAZZO RECESS (-U) = \$354.00 LIST ADDER			
CO Floor	CO-260		1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top		
	CO-260,3,4,6,8	\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		

Note: Spec 22 13 19 - 1;

CO Walls	CO-590-RD		1
	Watts - threaded brass cleanout plug with countersunk head, stainless steel access cover and vandal proof stainless steel screw		
	CO-590-RD,1.5	\$184.00	1
	Watts - 1-1/2"Ø (39 mm)		
	CO-590-RD,2	\$188.00	1
	Watts - 2"Ø (51 mm)		
	CO-590-RD,3	\$232.00	1
	Watts - 3"Ø (76 mm)		
	CO-590-RD,4	\$307.50	1
	Watts - 4"Ø (102 mm)		
	CO-590-RD,5	\$429.00	1
	Watts - 5"Ø (126 mm)		
	CO-590-RD,6	\$661.00	1
	Watts - 6"Ø (152 mm)		
	Note: Spec 22 13 19 - 1; equal to Smith 4472		
CO Exterior	CO-200-RX-4		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top		
	CO-200-RX-4,2	\$420.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-RX-4,3	\$487.50	1
	Watts - 3"Ø (76 mm)		
	CO-200-RX-4,4	\$596.50	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 22 13 19 - 2; equal to Smith 4220		
CO Exterior (Decorative Paving)	CO-200-RX		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, nickel bronze top		
	CO-200-RX,2	\$778.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-RX,3	\$815.50	1
	Watts - 3"Ø (76 mm)		
	CO-200-RX,4	\$1,036.00	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 22 13 19 - 2		
CO Exterior (Vehicular Traffic)	CO-300-MF	\$1,391.00	1
	Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top		
	CO-380		1
	Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		
	CO-380,2	\$96.25	1
	Watts - 2"Ø (51 mm)		
	CO-380,3	\$148.50	1
	Watts - 3"Ø (76 mm)		
	CO-380,4	\$205.50	1
	Watts - 4"Ø (102 mm)		

CO-380,6

\$420.50 1

Watts - 6"Ø (152 mm)

Note: Spec 22 13 19 - 2; equal to Smith 4250

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
Domestic BFP	LF909M1-QT : 2 Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391012)	\$3,363.00	1
	909-AGF Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	LF777SI : 2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
Note: Dwg AP1-1 Detail #3			
BFP Option	LF009M2-QT : 2 Watts - quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)	\$1,548.00	1
	909-AGF Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	LF777SI : 2 Watts - 2"Ø (51 mm) valve (0379116)	\$280.00	1
Note: Dwg AP1-1 Detail #3			
PF- E/B1/B2/B3	LFMMVM1-US : 3/4 Watts - Lead Free cast copper silicon alloy body, solid wax hydraulic principle thermostat, integral filter washers and check valves, ASSE 1069, ASSE 1070, ASSE 1017, cUPC AND IAPMO listed, valve shall control temperature from a low of 1/2gpm, 5gpm at 10psi and 8gpm at 20psi drop across the valve, 3/4"Ø valve, union solder (0559118)	\$391.50	1
	LFMMVM1-US : 1 Watts - Lead Free cast copper silicon alloy body, solid wax hydraulic principle thermostat, integral filter washers and check valves, ASSE 1069, ASSE 1070, ASSE 1017, cUPC AND IAPMO listed, valve shall control temperature from a low of 1/2gpm, 5gpm at 10psi and 8gpm at 20psi drop across the valve, 1"Ø valve, union solder (0559121)	\$515.00	1
Note: Dwg AP1-2 Plumbing Fixture Schedule & Dwg P6-0 Plumbing Fixtures Schedule (Notes #6)			

Section Brand: Delany

Label	Product No. Description	List Price	Qty.
PF-A/PF-B	PL1402-1.28 Delany - EXPOSED PULSAR VALVE for WATER CLOSET (BATTERY POWERED & SENSOR OPERATED} w/ SLIPFIT CONNECTION, 1.5" x 9" FLUSH CONNECTION, TOP SPUD, OVERRIDE BUTTON, & SWEAT ADAPTOR KIT (1.28 GPF}	\$552.10	1
Note: Dwg AP1-2 Plumbing Fixture Schedule			
PF-C	PL1451-0.5 Delany - EXPOSED PULSAR VALVE for URINAL (BATTERY POWERED & SENSOR OPERATED} w/ SLIPFIT CONNECTION, 0.75" x 9" FLUSH CONNECTION, TOP SPUD, OVERRIDE BUTTON, & SWEAT ADAPTOR KIT (0.5 GPF}	\$552.10	1
Note: Dwg AP1-2 Plumbing Fixture Schedule			

A1/A2	U402-1.6-SM	\$508.30	1
Delany - EXPOSED FLUSHBOY ULTRA VALVE for HIGH EFFICIENCY WATER CLOSET w/SIDEARM (Side Mounted Sensor Actuator), 1.5" x 9" FLUSH CONNECTION, TOPSPUD, SWEAT ADAPTOR KIT & SLIPFIT CONNECTION (1.6 GPF)			
Note: Dwg P6-0 Plumbing Fixtures Schedule; Equal to Sloan 111-1.6-SMO			
C1/C2	U451-1-SM	\$474.25	1
Delany - EXPOSED FLUSHBOY ULTRA VALVE for URINAL w/ 0.75" x 9" FLUSH CONNECTION, TOP SPUD, SWEAT ADAPTOR KIT, & SLIPFIT TAILPIECE (1.0 GPF)			
Note: Dwg P6-0 Plumbing Fixtures Schedule; Equal to Sloan 186-1-SMO			

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.