



**Address:** 7737 Reinhold Drive, **Phone:** (513) 861-1682  
 Cincinnati, Ohio, 45237 United States **Fax:** (513) 487-5337

**Quotation:**  
**Q-4032-S**

<b>To:</b>	<b>Contractor Holder Ohio</b> Cincinnati, Ohio	<b>Bid Date:</b>	2018-11-13
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2018-12-13
<b>Phone:</b>	800-542-1682	<b>Creator:</b>	Dave Evans , davee@disney-mclane.com
<b>Fax:</b>	877-476-1682	<b>Sales Rep.:</b>	Jason Plageman , jasonp@disney-mclane.com
		<b>Shipping Address:</b>	800 Amrine Mill Road , Marysville, Ohio, United States

**Job Name: Marysville Exempted Village Schools - High School Athletic Improvements**

**Engineer:** KLH Engineers, PSC **Architect:** MSA Architects

**Comments:**

**Section Brand: Watts Drainage**

Label	Product No. Description	List Price	Qty.
DF1	<b>CA-421</b> Watts - floor mounted plate type carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.	\$752.00	1
<i>Note: Dwg P-601 Plumbing Fixture Schedule</i>			
LV1	<b>TCA-411 Series</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	<b>TCA-411</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	<b>TCA-411-D</b> Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
<i>Note: Dwg P-601 Plumbing Fixture Schedule</i>			
UR1	<b>CA-321</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$839.00	1
<i>Note: Dwg P-601 Plumbing Fixture Schedule</i>			
WC1	<b>ISCA-101-L/R</b> Watts - single, horizontal, cast iron fitting, left/right side outlet	\$1,587.50	1
	<b>ISCA-101-D</b> Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support	\$2,967.00	1
	<b>ISCA-121</b> Watts - single, vertical, cast iron fitting	\$1,801.00	1

	<b>ISCA-121-D</b>	\$3,181.50	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts		
	<b>ISCA-131-L/R</b>	\$2,105.50	1
	Watts - single, vertical, cast iron fitting, left/right side outlet		
	<b>ISCA-131-D</b>	\$3,480.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support		
	<b>Note: Dwg P-601 Plumbing Fixture Schedule</b>		
	<i>Note: Quoted carriers are rated for 500 lbs. If higher weight rating is required, please contact Disney McLane for revised selections and pricing.</i>		
WH1	<b>HY-725-88</b>		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		
	<b>HY-725-88,-6,-8</b>	\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	<b>HY-725-88,-10,-12,-14</b>	\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	<b>HY-725-88,-16,-18</b>	\$1,829.50	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	<b>HY-725-88,-20,-22,-24</b>	\$1,870.00	1
	Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick		
	<b>Note: Dwg P-601 Plumbing Fixture Schedule; equal to Woodford B65</b>		
FD1/FD2	<b>FD-100-A5-6</b>		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter nickel bronze, adjustable round strainer, vandal proof		
	<b>FD-100-A5-6,2,3,4</b>	\$535.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>FD-100-A5-6,6</b>	\$656.00	1
	Watts - 6"Ø (152 mm)		
	<b>Note: Dwg P-601 Plumbing Drain Schedule; equal to Zurn Z415B</b>		
Water Hammer Arrester Bellows	<b>SS Series</b>		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	<b>SS-A</b>	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>SS-B</b>	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>SS-C</b>	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>SS-D</b>	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>SS-E</b>	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		

	<b>SS-F</b>	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note: Spec 221119 - 6/7</b>			
Water Hammer Arrestor Piston	<b>LF15M2-DR Series</b>		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	<b>LF15M2-A-DR</b>	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>LF15M2-B-DR</b>	\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>LF15M2-C-DR</b>	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>LF15M2-D-DR</b>	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>LF15M2-E-DR</b>	\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>LF15M2-F-DR</b>	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note: Spec 221119 - 6/7</b>			
Trap Primer	<b>LFTP300-DR Series</b>		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$270.00	1
	ATS - 1/2", Solder Inlet and Threaded Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
<b>Note: Spec 221119 - 7</b>			
Vent Cap	<b>RD-680-VC</b>		1
	Watts - cast iron, vandal proof cover		
	<b>RD-680-VC,2,3,4</b>	\$471.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-680-VC,6</b>	\$670.50	1
	Watts - 6"Ø (152 mm)		
	<b>RD-680-VC,8</b>	\$768.50	1
	Watts - 8"Ø (203 mm)		
<b>Note: Spec 221319 - 3</b>			

### Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
PRV	<b>3" LFM115 150 X FC AOS (Flanged connections)</b> Watts - PRV ( 2600-49 )	\$3,447.00	1
<b>Note: Dwg P-501 221113.00-02 - SOUTH BUILDING WATER SERVICE WITH DOMESTIC BOOSTER PUMP DETAIL</b>			
PRV	<b>4" LFF115 150 FCXAOS (Flanged connections)</b> Watts - PRV ( 4440-04 )	\$3,957.00	1

**Note: Dwg P-501 221113.00-03 - NORTH BUILDING WATER SERVICE DETAIL**

BFP1	<b>957-QT : 4</b>	\$4,580.00	1
	Watts - Reduced Pressure Zone Assembly, w/Quarter-Turn Ball Valves		
	<b>957-AG</b>	\$269.50	1
	Watts - 957-AG Air Gap (0111764)		
	<b>77F-DI-FDA-125 : 4</b>	\$1,042.00	1
	Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 4"Ø (102 mm) valve (0825212)		
	<b>Note:</b> Dwg P-601 Plumbing Fixture Schedule		
BFP2	<b>LF007M2-QT : 1 1/2</b>	\$883.00	1
	Watts - Lead Free cast copper silicon alloy body for 1/2" to 2" connections or fused epoxy coated cast iron body for 2-1/2" to 3" connections, replaceable seat and seat discs, resilient seated isolation valves, quarter turn ball-valves, 1-1/2"Ø (38 mm) pipe connection (0063234)		
	<b>Note:</b> Dwg P-601 Plumbing Fixture Schedule		
ET1	<b>PLT-12</b>	\$129.00	1
	Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 4.5 gallons (0067371)		
	<b>Note:</b> Dwg P-601 Plumbing Fixture Schedule; equal to Amtrol ST-12		
ET2	<b>DETA 42</b>	\$2,824.00	1
	Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 22 gallons (0212030)		
	<b>Note:</b> Dwg P-601 Plumbing Fixture Schedule; equal to Amtrol ST-30V		
HB1	<b>SC8-4</b>	\$81.25	1
	Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)		
	<b>Note:</b> Dwg P-601 Plumbing Fixture Schedule; equal to Woodford 24		
Clothes Washer Outlet Box	<b>2-M2DWB</b>	\$199.50	1
	Watts - brass body, 1/2" solder or compression connection, single lever, 3/4" hose connection outlets, 150 psi maximum pressure, 180° F maximum temperature, molded plastic enclosure with top and side knockouts, drain knock out to accommodate waste drain pipe (0006644 & 0006625)		
	<b>Note:</b> Spec 221119 - 4		

**Section Brand: Fiat**

Label	Product No. Description	List Price	Qty.
MS1	<b>MSBID2424</b>	\$324.00	1
	FIAT - MOP SERVICE BASIN WITH INTEGRAL DRAIN 24"		
	<b>830AA</b>	\$224.00	1
	FIAT - MOP SERVICE BASIN FAUCET		

**Note:** Dwg P-601 Plumbing Fixture Schedule; equal to Mustee 63M, 63.600A

**Section Brand: Armstrong**

Label	Product No. Description	List Price	Qty.
CP1/CP2	<b>Placeholder</b>		1
	<b>Note:</b> Dwg P-601 Plumbing Pump Schedule; equal to Taco 0014-F1		
DBP1	<b>Placeholder</b>		1

**Note:** Dwg P-601 Plumbing Pump Schedule; equal to SYNCROFLO 22DG05XXX-4H-XX-SWF55-1

**Section Brand: Powers**

Label	Product No. Description	List Price	Qty.
Point of use TMV	<b>LFE480-01</b> Powers - Lavatory Thermostatic Tempering Valves, 1/2" NPT inlets & outlet, Chrome Plated, Minimum Flow 0.5 gpm	\$332.00	1

**Note:** Spec 223001 - 1

**Special Terms:**

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.