



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United States **Fax:** (513) 487-5337

Quotation:
Q-4049-S

To:	Contractor Holder Indiana Cincinnati, Ohio	Bid Date:	2018-11-14
Attn.:	N/A	Expiry Date:	2018-12-14
Phone:	800-542-1682	Creator:	Dave Evans , davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Kevin Spearing , kevin@disney-mclane.com
		Shipping Address:	615 Adams St., 47403, Bloomington, Indiana, United States

Job Name: Monroe County Youth Services Bureau Addition - Bloomington IN

Engineer: AEC Engineering **Architect:** RQAW Architecture

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
UR-1	CA-321 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$839.00	1
<i>Note: P-601: Plumbing Fixture Schedule</i>			
EWC-1	CA-421 Watts - floor mounted plate type carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.	\$752.00	1
<i>Note: P-601: Plumbing Fixture Schedule</i>			
EWC-1	CA-431-1 Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.	\$1,215.00	1
<i>Note: P-601: Plumbing Fixture Schedule</i>			
FD-1	FD-102-A5 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer, 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet sizes	\$481.00	1
<i>Note: P-601: Plumbing Fixture Schedule; EQUAL TO: Jay R Smith 2005-A</i>			
FD-2	FD-102-ER5 Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, extended rim strainer, 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet sizes	\$1,037.00	1
<i>Note: P-601: Plumbing Fixture Schedule; EQUAL TO: Jay R Smith 2005-A-F</i>			
WH-1	HY-420 Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, seat casting and internal working parts, wall mount, bronze wall casing, chrome plated face, integral vacuum breaker		1
	HY-420,-4,-6,-8 Watts - 4" (102 mm), 6" (152 mm), 8" (203 mm) thick	\$864.50	1
	HY-420,-10,-12,-14 Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick	\$1,006.00	1
	HY-420-16 Watts - 16" (406 mm) thick	\$1,146.50	1

Note: P-601: Plumbing Fixture Schedule; EQUAL TO: Woodford 67

WHA Bellows	SS Series Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		1
	SS-A Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$549.50	1
	SS-B Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$1,119.00	1
	SS-C Watts - 33-60, fixture units, 1" (25 mm) connection	\$1,672.00	1
	SS-D Watts - 61-113 fixture units, 1" (25 mm) connection	\$4,191.00	1
	SS-E Watts - 114-154 fixture units, 1" (25 mm) connection	\$4,731.50	1
	SS-F Watts - 155-330 fixture units, 1" (25 mm) connection	\$5,815.00	1
Note: P-601: Water Hammer Arrestor Schedule; Quoting Bellows Option.			
WHA Piston	LF15M2-DR Series Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		1
	LF15M2-A-DR Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$175.00	1
	LF15M2-B-DR Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$336.00	1
	LF15M2-C-DR Watts - 33-60, fixture units, 1" (25 mm) connection	\$529.50	1
	LF15M2-D-DR Watts - 61-113 fixture units, 1" (25 mm) connection	\$1,118.00	1
	LF15M2-E-DR Watts - 114-154 fixture units, 1" (25 mm) connection	\$1,390.50	1
	LF15M2-F-DR Watts - 155-330 fixture units, 1" (25 mm) connection	\$1,656.00	1
Note: P-601: Water Hammer Arrestor Schedule; Spec 22 11 19 - 7			
NFWH	HY-725-88 Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		1
	HY-725-88,-6,-8 Watts - 6" (152 mm), 8" (203 mm) thick	\$1,547.00	1
	HY-725-88,-10,-12,-14 Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick	\$1,690.00	1
	HY-725-88,-16 Watts - 16" (406 mm) thick	\$1,829.50	1
Note: Spec 22 11 19 - 6			

MCWH	HY-330	\$1,349.00	1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, warm climate hydrant, all bronze head, seat casting and internal working parts, wall mount, concealed, integral vacuum breaker, nickel bronze box and door, chrome plated face, 6-7/16" x 5-7/16" (164 mm x 138 mm), loose key		
	Note: Spec 22 11 19 - 7		
WCO	CO-460-RD		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$364.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$417.50	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$611.50	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 22 13 19 - 2		
PVC-CO	CO-200-R-60		1
	Watts - 7" (178 mm) diameter, PVC body with poly plug, 5" (127 mm) round, nickel bronze top		
	CO-200-R-60,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-R-60,3	\$661.00	1
	Watts - 3"Ø (76 mm)		
	CO-200-R-60,4	\$881.00	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 22 13 19 - 2; CARPET CLAMPING FLANGE (-CF) = \$285.00 LIST ADDER CARPET MARKER (-RC) = \$78.00 LIST ADDER NB HEAVY DUTY (-RX) = \$155.00 LIST ADDER TILE RECESS (-T) = NO ADDITIONAL TERRAZZO RECESS (-U) = \$354.00 LIST ADDER		
FD-1	FD-100-A6-60-5-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" (152 mm) diameter, nickel bronze, round strainer, PVC Body w/Socket Outlet (2,3,4" Only), sediment bucket, trap primer tapping		
	FD-100-A6-60-5-7,2,3,4	\$697.00	1
	Watts - 2" (51mm),3" (76mm), 4" (102mm) outlet size		
	Note: Spec 22 13 19 - 3;		
FD-2	FD-100-A5-60-7		1
	Watts - 8-1/8" (206 mm) diameter PVC body socket outlet, 5" (127 mm) diameter, nickel bronze, round strainer, trap primer tapping.		
	FD-100-A5-60-7,2,3,4	\$481.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	Note: Spec 22 13 19 - 3;		
VENT CAP	RD-680-VC		1
	Watts - cast iron, vandal proof cover		
	RD-680-VC,2,3,4	\$471.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-680-VC,6	\$670.50	1
	Watts - 6"Ø (152 mm)		

	RD-680-VC,8	\$768.50	1
	Watts - 8"Ø (203 mm)		
Note: Spec 22 13 19 - 3;			
EXPANSION JOINT	RD-900		1
	Watts - neoprene expansion joint, no hub (MJ) clamps		
	RD-900,2	\$298.00	1
	Watts - 2"Ø (51 mm)		
	RD-900,3	\$345.50	1
	Watts - 3"Ø (76 mm)		
	RD-900,4	\$404.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 13 19 - 3;			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
HB-1	SC8-4 Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)	\$81.25	1
Note: P-601: Plumbing Fixture Schedule; EQUAL TO: Woodford 24P-3/4			
BFP-1	LF919-QT : 2 Watts - Lead Free cast copper silicon alloy body, corrosion resistant plastic guide, replaceable seat and seat discs pressure differential relief valve located in the zone between check valves, push-in type with internal sensing line and bronze cover, resilient seated isolation valves, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0065376)	\$1,626.00	1
	919AGC Watts - Air Gaps, Elbows and Test Cocks for Reduced Pressure Zone Assemblies, 2-3/8" (60mm) x 3-1/8"(79mm)	\$99.00	1
	LF777SI : 2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
Note: P-601: Backflow Preventer Schedule			
BFP-1 OPT.	LF009M2-QT : 2 Watts - quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)	\$1,548.00	1
	909-AGF Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	LF777SI : 2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
Note: P-601: Backflow Preventer Schedule; Quoting as an Alternate Option.			
ET-1	DETA 12 Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 5 gallons (0212027)	\$2,109.00	1
Note: P-601: Backflow Preventer Schedule; EQUAL TO: Armstrong AST-12			
WMB-1	2-M2DWB Watts - brass body, 1/2" solder or compression connection, single lever, 3/4" hose connection outlets, 150 psi maximum pressure, 180° F maximum temperature, molded plastic enclosure with top and side knockouts, drain knock out to accommodate waste drain pipe (0006644 & 0006625)	\$199.50	1
Note: Spec 22 11 19 - 4			

Section Brand: Ames

Label	Product No. Description	List Price	Qty.
BFP-2	3000SS-OSY-GPM : 4 Ames - Double Check Detector Assemblies, UL/FM outside stem and yoke resilient seated gate valves, 4"(100mm)	\$5,827.00	1
	8000F : 4 Ames - Stainless Steel Flanged Strainer, 304 stainless steel, standard screen, 4"(100mm)	\$595.50	1

Note: P-601: Backflow Preventer Schedule;

Section Brand: Delany

Label	Product No. Description	List Price	Qty.
UR-1	U451-0.125 Delany - EXPOSED FLUSHBOY ULTRA VALVE forHIGH EFFICIENCY URINAL w/ 0.75" x 9" FLUSH CONNECTION, TOP SPUD, SWEAT ADAPTOR KIT, & SLIPFIT TAILPIECE (0.125 GPF}	\$175.00	1

Note: P-601: Plumbing Fixture Schedule; EQUAL TO: Royal 186-0.125

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
TMV-1	ETV200AE000 Powers - HydroGuard XP Emergency Tempering Valve with Cold Water Bypass, Rough Bronze, Bottom/Top	\$2,040.00	1

Note: P-601: Thermostatic Mixing Valve Schedule; Model Specified is incomplete, Quoting full model based on description.

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.