



**Address:** 7737 Reinhold Drive, **Phone:** (513) 861-1682  
 Cincinnati, Ohio, 45237 United States **Fax:** (513) 487-5337

**Quotation:**  
**Q-4064-S**

<b>To:</b>	<b>Contractor Holder Indiana</b> Cincinnati, Ohio	<b>Bid Date:</b>	2018-11-19
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2018-12-19
<b>Phone:</b>	800-542-1682	<b>Creator:</b>	Dave Evans, davee@disney-mclane.com
<b>Fax:</b>	877-476-1682	<b>Sales Rep.:</b>	Rick Bayne, rickb@disney-mclane.com
		<b>Shipping Address:</b>	, Winchester, Indiana, United States

**Job Name: Randolph County Highway Department Maintenance Facility**

**Engineer:** HWC Engineering **Architect:** Cripe Architects + Engineers

**Comments:**

**Section Brand: Watts Drainage**

Label	Product No. Description	List Price	Qty.
P-2	<b>CA-321</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$839.00	1
<i>Note: Dwg P001 Plumbing Fixture Schedule</i>			
P-4	<b>TCA-411 Series</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	<b>TCA-411</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	<b>TCA-411-D</b> Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
<i>Note: Dwg P001 Plumbing Fixture Schedule</i>			
P-7	<b>CA-421</b> Watts - floor mounted plate type carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.	\$752.00	1
<i>Note: Dwg P001 Plumbing Fixture Schedule</i>			
P-12	<b>HY-725-88</b> Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		1
	<b>HY-725-88,-6,-8</b> Watts - 6" (152 mm), 8" (203 mm) thick	\$1,547.00	1
	<b>HY-725-88,-10,-12,-14</b> Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick	\$1,690.00	1
	<b>HY-725-88,-16,-18</b> Watts - 16" (406 mm), 18" (457 mm) thick	\$1,829.50	1
	<b>HY-725-88,-20,-22,-24</b> Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick	\$1,870.00	1

*Note: Dwg P001 Plumbing Fixture Schedule; equal to Woodford B65*

P-13	<b>HY-800</b>		1
	Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, yard hydrant with and lift handle and lock option, 1/8" NPT drain port		
	<b>HY-800-1</b>	\$1,100.00	1
	Watts - 1' (305 mm) depth		
	<b>HY-800-2</b>	\$1,161.00	1
	Watts - 2' (610 mm) depth		
	<b>HY-800-3</b>	\$1,223.00	1
	Watts - 3' (914 mm) depth		
	<b>HY-800-4</b>	\$1,290.00	1
	Watts - 4' (1219 mm) depth		
	<b>HY-800-5</b>	\$1,349.00	1
	Watts - 5' (1524 mm) depth		
	<b>HY-800-6</b>	\$1,411.00	1
	Watts - 6' (1829 mm) depth		
	<b>Note:</b> Dwg P001 Plumbing Fixture Schedule; equal to Woodford Y2		
	Note: Hydrant does not come with backflow protection.		
FD-1	<b>FD-100-A5</b>		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer		
	<b>FD-100-A5,2,3,4</b>	\$481.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>FD-100-A5,6</b>	\$601.00	1
	Watts - 6"Ø (152 mm)		
	<b>Note:</b> Dwg P001 Drain Schedule; equal to Smith 2005		
	Note: Trap guard by others		
FCO-1	<b>CO-200-RX-C</b>		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, nickel bronze top, membrane clamp		
	<b>CO-200-RX-C,2</b>	\$884.50	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200-RX-C,3</b>	\$921.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200-RX-C,4</b>	\$1,142.00	1
	Watts - 4"Ø (102 mm)		
	<b>Note:</b> Dwg P001 Drain Schedule & Spec 221319 - 1/2; equal to Smith 4100		
WCO-1	<b>CO-300-R6</b>	\$349.50	1
	Watts - scoriated, round, access cover, nickel bronze, concealed mounting flanges, 6-1/4" (159 mm) Ø		
	<b>Note:</b> Dwg P001 Drain Schedule; equal to Smith 4720		
GCO-1	<b>CO-300-MF</b>	\$1,391.00	1
	Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top		
	<b>CO-380</b>		1
	Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		
	<b>CO-380,2</b>	\$96.25	1
	Watts - 2"Ø (51 mm)		

	<b>CO-380,3</b>	\$148.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-380,4</b>	\$205.50	1
	Watts - 4"Ø (102 mm)		
	<b>CO-380,6</b>	\$420.50	1
	Watts - 6"Ø (152 mm)		

**Note:** Dwg P001 Drain Schedule; equal to Smith 4250

TD-1 thru to TD-8	<b>DX-DI</b>	\$1,133.00	1
	Watts - UV stabilized talc-filled polypropylene channels with 6" (152 mm) no-hub bottom or end outlet(s), pre-sloped trench, 12" (305 mm) wide, including frame connectors, grate lockdowns and construction covers, ductile iron frame, framed anchored grate, ductile iron, Class F		
	<b>CB-2424-DI</b>	\$3,695.00	1
	Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) and 6" (152 mm) no hub bottom outlets, 24" (610 mm) wide, 24" (610 mm) long, ductile iron grate, Class F		

**Note:** Dwg P001 Drain Schedule; equal to Smith 9878

Note: Requested drain is 10 inches wide and Polymer Concrete where the quoted is 12 inches wide and Polypropylene. Also, cannot match catch basin dimensions.

Please note trench drain price is per foot.

Water Hammer Arrestor	<b>SS Series</b>		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	<b>SS-A</b>	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>SS-B</b>	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>SS-C</b>	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>SS-D</b>	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>SS-E</b>	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>SS-F</b>	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		

**Note:** Dwg P001 Water Hammer Arrestor Schedule; equal to Smith 5000 series

Moderate Climate Wall hydrant	<b>HY-330-3</b>	\$1,349.00	1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, warm climate hydrant, all bronze head, seat casting and internal working parts, wall mount, concealed, integral vacuum breaker, stainless steel box and door, chrome plated face, 6-7/16" x 5-7/16" (164 mm x 138 mm), loose key		

**Note:** Spec 221119 - 7/8

Note: Quoting stainless steel in lieu of chrome plated

Water Hammer Arrestor	<b>LF15M2-DR Series</b>		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	<b>LF15M2-A-DR</b>	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>LF15M2-B-DR</b>	\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		

	<b>LF15M2-C-DR</b>	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>LF15M2-D-DR</b>	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>LF15M2-E-DR</b>	\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>LF15M2-F-DR</b>	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note:</b> Spec 221119 - 8			
Trap	<b>LFTP300-DR Series</b>		1
Primer	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$270.00	1
	ATS - 1/2", Solder Inlet and Threaded Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
<b>Note:</b> Spec 221119 - 8			

### Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
EX-1	<b>PLT-12</b> Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 4.5 gallons (0067371)	\$129.00	1
<b>Note:</b> Dwg P001 Plumbing Equipment Schedule; equal to Amtrol ST-12			
MIX-1	<b>LFMMVM1-UT : 1/2</b> Watts - Lead Free cast copper silicon alloy body, solid wax hydraulic principle thermostat, integral filter washers and check valves, ASSE 1069, ASSE 1070, ASSE 1017, cUPC AND IAPMO listed, valve shall control temperature from a low of 1/2gpm, 5gpm at 10psi and 8gpm at 20psi drop across the valve, 1/2"Ø valve, union thread (0559116)	\$314.00	1
<b>Note:</b> Dwg P001 Plumbing Equipment Schedule; equal to Symmons 5-120			
BFP	<b>LF009M2-QT : 1</b> Watts - quarter turn ball-valves, 1"Ø (25 mm) pipe connection (0391004)	\$708.50	1
	<b>909-AGC</b> Watts - 909-AGC Air Gap (0881376)	\$106.50	1
	<b>LF777SI : 1</b> Watts - 1"Ø (25 mm) valve (0379113)	\$93.50	1
<b>Note:</b> Dwg P201 Building B - Admin and Maintenance - Piping Plan Note: Quoted as per line size, no model number given. Quoting as suggestion.			

### Section Brand: Delany

Label	Product No. Description	List Price	Qty.
P-2	<b>S451-1-SM</b> Delany - EXPOSED SABER VALVE for URINAL w/ SLIPFIT CONNECTION, 0.75" x 9" FLUSH CONNECTION,(1.0 GPF),SIDEARM BATTERY POWERED, SENSOR ACTIVATED, OVER the HANDLE RETRO-FIT KIT for EXPOSED WATER CLOSET & URINAL FLUSHMETERS	\$459.25	1
<b>Note:</b> Dwg P001 Plumbing Fixture Schedule; equal to Sloan 186-1-SMO			

**Section Brand: Powers**

Label	Product No. Description	List Price	Qty.
P-6	<p><b>P910HK1U</b></p> <p>Powers - Pressure Balancing Mixing Valve, integral check/service stops, handle rotation limit stop, reversible inlets, four-port connections, poppet/diaphragm cartridge construction, 1/2" copper sweat connections, Standard Chrome-Plated Brass, Arm &amp; Flange, Diverter, Chrome Plated 1/2" Slip-Fit</p>	\$424.00	1

**Note:** Dwg P001 Plumbing Fixture Schedule;

*THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID*

MIX-2	<p><b>LFLM490-1</b></p> <p>Powers - 1/2 LFLM490-1</p>	\$295.00	1
-------	---	----------	---

**Note:** Dwg P001 Plumbing Equipment Schedule;

*Note: This is not a Hi/Lo valve but meets the flow requirements.*

**Special Terms:**

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.