



**Address:** 7737 Reinhold Drive, **Phone:** (513) 861-1682  
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337  
 States

**Quotation:**  
**Q-4083-S**

<b>To:</b>	<b>Contractor Holder Ohio</b> Cincinnati, Ohio	<b>Bid Date:</b>	2018-11-20
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2018-12-20
<b>Phone:</b>	800-542-1682	<b>Creator:</b>	Dave Evans , davee@disney-mclane.com
<b>Fax:</b>	877-476-1682	<b>Sales Rep.:</b>	Kim Metzger , kimm@disney-mclane.com
		<b>Shipping Address:</b>	1 Comtex Way, Ashland, Ohio, United States

**Job Name: COMTEX - Commercial Laundry Facility**

**Engineer:** Dynamix Engineering Ltd - Columbus **Architect:** M+A Architects

**Comments:**

**Section Brand: Watts Drainage**

Label	Product No. Description	List Price	Qty.
FD1	<b>FD-103-A7</b> Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 7" (178 mm) diameter, nickel bronze, adjustable round strainer, 3"Ø (76 mm)	\$680.00	1
<i>Note: P6.1 - Plumbing Drain &amp; Cleanout Schedule &amp; Roughin-In; Equal to Zurn ZN415.</i>			
FD2	<b>FD-344-Y-1-5</b> Watts - 12-1/2" (318 mm) diameter cast iron body no-hub outlet, 12-1/2" (318 mm) diameter, nickel bronze, 4"(102 mm), round grate, sediment bucket	\$2,052.00	1
<i>Note: P6.1 - Plumbing Drain &amp; Cleanout Schedule &amp; Roughin-In; Equal to Zurn ZN505</i>			
FS1	<b>FS-740-175</b> Watts - cast iron body, 8-1/4" (209 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, porcelain enamel coated cast iron grate, 3/4 grate		1
	<b>FS-740-175,2,3,4</b> Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size	\$2,227.00	1
<i>Note: P6.1 - Plumbing Drain &amp; Cleanout Schedule &amp; Roughin-In; Equal to Zurn Z1901-3</i>			
TD	<b>P-DI</b> Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) no-hub bottom outlet, pre-sloped trench, pre-sloped trench, 6" (152 mm) wide, including frame connectors, grate lockdowns and construction covers, UV stabilized glass-filled polypropylene frame, framed anchored grate, ductile iron, Class C	\$432.50	1
<i>Note: P6.1 - Plumbing Drain &amp; Cleanout Schedule &amp; Roughin-In. Please note trench drain price is per foot. Note: Polypropylene channel in lieu of polyethylene channel. THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID</i>			
TD (option)	<b>FG-GV</b> Watts - Frame Guard, Galvanized Steel Frame Guard	\$65.75	1
<i>Note: P6.1 - Plumbing Drain &amp; Cleanout Schedule &amp; Roughin-In. Please note trench drain price is per foot. THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID</i>			
FCO	<b>CO-200-R</b> Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		1
	<b>CO-200-R,2</b> Watts - 2"Ø (51 mm)	\$625.50	1

	<b>CO-200-R,3</b>	\$661.00	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200-R,4</b>	\$881.00	1
	Watts - 4"Ø (102 mm)		
<b>Note:</b> P6.1 - Plumbing Drain & Cleanout Schedule & Roughin-In; Equal to Zurn ZN1400			
<i>Note: Custom Markings on the cover for an additional cost of \$ to List</i>			
FCO	<b>CO-260</b>		1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top		
	<b>CO-260,3,4,6,8</b>	\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		
<b>Note:</b> P6.1 - Plumbing Drain & Cleanout Schedule & Roughin-In			
GCO	<b>CO-200-RX-4-6</b>		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top, vandal proof		
	<b>CO-200-RX-4-6,2</b>	\$517.00	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200-RX-4-6,3</b>	\$584.00	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200-RX-4-6,4</b>	\$692.50	1
	Watts - 4"Ø (102 mm)		
<b>Note:</b> P6.1 - Plumbing Drain & Cleanout Schedule & Roughin-In; Equal to Zurn Z1406-VP.			
<i>Note: Custom Markings on the cover for an additional cost of \$ to List</i>			
EWC1	<b>CA-431-1</b>	\$1,215.00	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
<b>Note:</b> P6.1 - Plumbing Equipment & Rough-In Schedule			
UR	<b>CA-321</b>	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
<b>Note:</b> P6.1 - Plumbing Fixture & Rough-In Schedule.			
L1/S1	<b>TCA-411 Series</b>		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>TCA-411</b>	\$989.50	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>TCA-411-D</b>	\$1,411.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
<b>Note:</b> P6.1 - Plumbing Fixture & Rough-In Schedule.			
WH1	<b>HY-725</b>		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door		
	<b>HY-725,-6,-8</b>	\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		

	<b>HY-725,-10,-12,-14</b>	\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	<b>HY-725,-16,-18</b>	\$1,830.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
<b>Note: P6.1 - Plumbing Fixture &amp; Rough-In Schedule; Equal to Zurn Z1300</b>			
Moderate Climate Hydrant	<b>HY-330</b>	\$1,349.00	1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, warm climate hydrant, all bronze head, seat casting and internal working parts, wall mount, concealed, integral vacuum breaker, nickel bronze box and door, chrome plated face, 6-7/16" x 5-7/16" (164 mm x 138 mm), loose key		
<b>Note: Spec 22 11 19 - 7.</b>			
<i>Note: Quoting as suggestion.</i>			
WHA	<b>LF15M2-DR Series</b>		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	<b>LF15M2-A-DR</b>	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>LF15M2-B-DR</b>	\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>LF15M2-C-DR</b>	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>LF15M2-D-DR</b>	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>LF15M2-E-DR</b>	\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>LF15M2-F-DR</b>	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
<b>Note: Spec 22 11 19 - 7.</b>			
Trap Primer	<b>LFTP300-DR Series</b>		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	<b>LFTP300T</b>	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	<b>LFTP300S</b>	\$270.00	1
	Watts - 1/2", Solder Inlet and Threaded Outlet Connect		
	<b>LFTP300-DU-DR</b>	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
<b>Note: Spec 22 11 19 - 9</b>			
Vent Caps	<b>RD-680-VC</b>		1
	Watts - cast iron, vandal proof cover		
	<b>RD-680-VC,2,3,4</b>	\$471.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-680-VC,6</b>	\$670.50	1
	Watts - 6"Ø (152 mm)		
	<b>RD-680-VC,8</b>	\$768.50	1
	Watts - 8"Ø (203 mm)		
<b>Note: Spec 22 13 19 - 6</b>			
Expansion Joints	<b>RD-900</b>		1
	Watts - neoprene expansion joint, no hub (MJ) clamps		

<b>RD-900,2</b>	\$298.00	1
Watts - 2"Ø (51 mm)		
<b>RD-900,3</b>	\$345.50	1
Watts - 3"Ø (76 mm)		
<b>RD-900,4</b>	\$404.00	1
Watts - 4"Ø (102 mm)		

**Note:** Spec 22 13 19 - 6

### Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
BFP1	<b>LF909-OSY-S-FDA : 3</b> Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, UL/FM outside stem & yoke gate valve, flange connections, FDA epoxy coated strainer, 3"Ø (76 mm) pipe connection (0122807)	\$10,216.00	1
	<b>909-AGK</b> Watts - 909-AGK Air Gap (0881385)	\$408.50	1

**Note:** P6.1 - Plumbing Equipment & Rough-In Schedule & P7.1 - Domestic Water Service Riser

BFP1 (alternate)	<b>957-OSY : 3</b> Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 3"Ø (76 mm) pipe connection (0111585)	\$4,700.00	1
	<b>957-AG</b> Watts - 957-AG Air Gap (0111764)	\$269.50	1
	<b>77F-DI-FDA-125 : 3</b> Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 3"Ø (76 mm) valve (0825211)	\$680.50	1

**Note:** P6.1 - Plumbing Equipment & Rough-In Schedule & P7.1 - Domestic Water Service Riser

BFP2	<b>LF919-QT-S : 2</b> Watts - Lead Free cast copper silicon alloy body, corrosion resistant plastic guide, replaceable seat and seat discs pressure differential relief valve located in the zone between check valves, push-in type with internal sensing line and bronze cover, resilient seated isolation valves, quarter turn ball-valves, bronze strainer, 2"Ø (51 mm) pipe connection (0065382)	\$1,972.00	1
	<b>919AGF</b> Watts - Air Gaps, Elbows and Test Cocks for Reduced Pressure Zone Assemblies, 4-1/2" (111mm) x 8-1/2"(216mm)(0881577)	\$208.00	1

**Note:** P6.1 - Plumbing Equipment & Rough-In Schedule

BFP2	<b>LF009M2-QT : 2</b> Watts - quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)	\$1,548.00	1
	<b>909-AGF</b> Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	<b>LF777SI : 2</b> Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1

**Note:** P6.1 - Plumbing Equipment & Rough-In Schedule

TXT	<b>DETA 30</b> Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 15 gallons (0212029)	\$2,644.00	1
-----	--	------------	---

**Note:** P6.1 - Plumbing Equipment & Rough-In Schedule; Equal to Amtrol ST-30VC

BFP1 (6")	<b>957-OSY : 6</b>	\$8,275.00	1
Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 6"Ø (152 mm) pipe connection (0111587)			

	<b>957-AG</b>	\$269.50	1
Watts - 957-AG Air Gap (0111764)			

	<b>77F-DI-FDA-125 : 6</b>	\$1,958.00	1
Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 6"Ø (152 mm) valve (0825214)			

**Note:** P7.1 - Domestic Water Service Riser.  
Note: Quoting as per detail.

DCDA	<b>757DCDA-OSY-CFM : 6</b>	\$6,974.00	1
Watts - 304 schedule 40 stainless steel housing and sleeve with groove end connections, reversible elastomeric discs, UL/FM outside stem & yoke gate valve, flange connections, cubic feet per minute reading, 6"Ø (152 mm) pipe connection (0111547)			

**Note:** FP0.0 - Fire Protection Equipment Schedule.  
Note: Tamper switches to be provided by others.

**Section Brand: Delany**

Label	Product No. Description	List Price	Qty.
-------	----------------------------	------------	------

WC1/WC2	<b>PL1402-1.6</b>	\$552.10	1
Delany - EXPOSED PULSAR VALVE for WATER CLOSET (BATTERY POWERED & SENSOR OPERATED} (1.6gpf)			

**Note:** P6.1 - Plumbing Fixture & Rough-In Schedule.  
THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID

UR	<b>PL1451-1</b>	\$552.10	1
Delany - EXPOSED PULSAR VALVE for URINAL (BATTERY POWERED & SENSOR OPERATED (1.0 gpf)			

**Note:** P6.1 - Plumbing Fixture & Rough-In Schedule.  
THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID

**Section Brand: Powers**

Label	Product No. Description	List Price	Qty.
-------	----------------------------	------------	------

L1 (mixing valve ASSE 1070)	<b>LFE480-10</b>	\$284.00	1
Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish			

**Note:** P6.1 - Plumbing Fixture & Rough-In Schedule.  
Note: Quoting as suggestion.

EFW (mixing valve)	<b>ES150-11</b>	\$1,126.00	1
Powers - ES150 EMERGENCY TEMPER			

**Note:** P6.1 - Plumbing Fixture & Rough-In Schedule; Equal to Bradley S19-2000.

EWDS (mixing valve)	<b>ETV400-15</b>	\$2,779.00	1
Powers - ETV400-15 EMERGENCY Tmpr			

**Note:** P6.1 - Plumbing Fixture & Rough-In Schedule; Equal to Bradley S19-2200.

**Section Brand: Fiat**

Label	Product No. Description	List Price	Qty.
MB1	<b>TSB-300</b> FIAT - 32" X 32" X 12" SS CURB	\$1,014.00	1

**Note:** P6.1 - Plumbing Fixture & Rough-In Schedule.

**Special Terms:**

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.