



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337
 States

Quotation:
Q-4244-S

To:	Contractor Holder Indiana Cincinnati, Ohio	Bid Date:	2018-12-13
Attn.:	N/A	Expiry Date:	2019-01-12
Phone:	800-542-1682	Creator:	Dave Evans , davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Kevin Spearing , kevin@disney-mclane.com
		Shipping Address:	Vincennes University, Vincennes, Indiana, United States

Job Name: Vincennes University Shake Learning Resources Center

Architect: Gibraltar Design

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
LAV-2	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
Note: P-301 - Plumbing Fixture Schedule			
WC-1	ISCA-101-L/R Watts - single, horizontal, cast iron fitting, left/right side outlet	\$1,587.50	1
	ISCA-101-D Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support	\$2,967.00	1
	ISCA-121 Watts - single, vertical, cast iron fitting	\$1,801.00	1
	ISCA-121-D Watts - double, vertical, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts	\$3,181.50	1
	ISCA-131-L/R Watts - single, vertical, cast iron fitting, left/right side outlet	\$2,105.50	1

	ISCA-131-D	\$3,479.50	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support		
Note: P-301 - Plumbing Fixture Schedule			
WC-2	ISCA-102-L/R		1
	Watts - horizontal, cast iron fitting, 4"Ø, no hub waste connection, left/right side outlet, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, epoxy coated, ductile iron, foot support		
	ISCA-102-D	\$8,950.00	1
	Watts - double, horizontal, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, epoxy coated, ductile iron, foot support		
	ISCA-122	\$5,108.00	1
	Watts - single, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, , 2"Ø, no hub vent connection. epoxy coated ductile iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, ductile iron foot support		
	ISCA-122-D	\$9,847.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, , 2"Ø, no hub vent connection. epoxy coated ductile iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, ductile iron foot support		
	ISCA-132-L/R	\$5,413.50	1
	Watts - single, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection and 4" Ø no hub side inlets, left/right side outlet, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, ductile iron foot support		
	ISCA-132-D	\$10,146.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection and 4" Ø no hub side inlets, , 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, ductile iron foot support		
Note: P-301 - Plumbing Fixture Schedule			
UR-1/UR-2	CA-321	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
Note: P-301 - Plumbing Fixture Schedule			
FD-1	FD-100-M6-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" x 6" (152 mm x 152 mm) nickel bronze, square strainer, trap primer connection		
	FD-100-M6-7,2,3,4	\$716.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-M6-7,6	\$836.50	1
	Watts - 6"Ø (152 mm)		
Note: P-301 - Plumbing Fixture Schedule; Equal to JR Smith 2030			
<i>Note: Trap seal to be provided by others.</i>			
FD-2	FD-450-5		1
	Watts - cast iron body, body collar with weepholes, no-hub outlet, 15-5/8" (397 mm) square, ductile iron, grate, sediment bucket		

	FD-450-5,2,3,4,5,6,8	\$3,142.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm), 5"Ø (127 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		
	Note: P-301 - Plumbing Fixture Schedule; Equal to JR Smith 2488 Note: Trap seal to be provided by others.		
FS-1	FS-790-5-F4-1		1
	Watts - 14 gauge type 304 stainless steel receptor body, 8-1/4" (210 mm) deep, no-hub outlet, dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, cast stainless steel, sediment bucket, 4" Round Nickel Bronze Funnel		
	FS-790-5-F4-1,2,3,4	\$4,736.50	1
	Watts - 2", 3", 4"		
	Note: P-301 - Plumbing Fixture Schedule. Note: Quoting 8" depth in lieu of 10" depth. Note: Quoting stainless steel top in lieu of nickel bronze top. THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID		
TD-1	D-DI	\$522.50	1
	Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) no-hub bottom outlet(s), pre-sloped trench, 6" (152 mm) wide, including frame connectors, grate lockdowns and construction covers, ductile iron frame, framed anchored grate, ductile iron, Class F		
	Note: P-301 - Plumbing Fixture Schedule. Please note trench drain price is per foot. Note: Quoting 6" width in lieu of 8" width.		
TD-1 (option)	FG-GV	\$65.75	1
	Watts - Frame Guard, Galvanized Steel Frame Guard		
	Note: P-301 - Plumbing Fixture Schedule. Please note trench drain price is per foot.		
DF-1/DF-2	CA-421	\$752.00	1
	Watts - floor mounted plate type carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
	Note: P-301 - Plumbing Fixture Schedule.		
HB-1	HY-420		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, seat casting and internal working parts, wall mount, bronze wall casing, chrome plated face, integral vacuum breaker		
	HY-420,-4,-6,-8	\$864.50	1
	Watts - 4" (102 mm), 6" (152 mm), 8" (203 mm) thick		
	HY-420,-10,-12,-14	\$1,006.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-420,-16,-18	\$1,146.50	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	Note: P-301 - Plumbing Fixture Schedule. Note: Quoting as suggestion, specified model not found.		
FCO	CO-200X-R		1
	Watts - 7" (178 mm) diameter, cast iron body inside caulk outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200X-R,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200X-R,3	\$661.00	1
	Watts - 3"Ø (76 mm)		
	CO-200X-R,4	\$881.00	1
	Watts - 4"Ø (102 mm)		

Note: P-301 - Plumbing Fixture Schedule; Equal to Josam 56000
Note: Watts CO can come with Custom Markings on the cover for an additional cost of \$\$ to List

FCO	CO-260		1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top		
	CO-260,3,4,6,8	\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		
Note: P-301 - Plumbing Fixture Schedule			
Roof Drain	RD-300-D-F		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387 mm) diameter, polyethylene dome, underdeck clamp, adjustable extension flange		
	RD-300-D-F,2,3,4	\$1,608.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-300-D-F,5,6	\$1,910.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	RD-300-D-F,8,10	\$2,213.00	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		
Note: P-301 - Plumbing Fixture Schedule			
WHA	LF15M2-DR Series		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: Spec 22 1119 - 4			
CO	CO-200-RX-4		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top		
	CO-200-RX-4,2	\$420.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-RX-4,3	\$487.50	1
	Watts - 3"Ø (76 mm)		
	CO-200-RX-4,4	\$596.50	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 1; Equal to Sioux Chief 851			
<i>Note: Quoting as per model number.</i>			
CO	CO-460		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		
	CO-460,2	\$228.00	1
	Watts - 2"Ø (51 mm)		
	CO-460,3	\$284.00	1
	Watts - 3"Ø (76 mm)		

	CO-460,4	\$441.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 1.			
<i>Note: Quoting as per description.</i>			
FCO	CO-200P-R-60		1
	Watts - 7" (178 mm) diameter, PVC body with poly plug, 5" (127 mm) round, nickel bronze top, Push-On Outlet		
	CO-200P-R-60,2	\$625.50	1
	Watts - 2" (51mm)		
	CO-200P-R-60,3	\$661.00	1
	Watts - 3" (76mm)		
	CO-200P-R-60,4	\$881.00	1
	Watts - 4" (102mm)		
Note: Spec 22 1319 - 2; Equal to Sioux Chief 852			
FCO	CO-260		1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top		
	CO-260,3,4,6,8	\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		
Note: Spec 22 1319 - 2			
WCO	CO-460-RD		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$364.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$417.50	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$611.50	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 2; Equal to Josam 58790			
Vent Caps	RD-680-VC		1
	Watts - cast iron, vandal proof cover		
	RD-680-VC,2,3,4	\$471.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-680-VC,6	\$670.50	1
	Watts - 6"Ø (152 mm)		
	RD-680-VC,8	\$768.50	1
	Watts - 8"Ø (203 mm)		
Note: Spec 22 1319 - 3			
Cleanout	CO-200-R		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200-R,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-R,3	\$661.00	1
	Watts - 3"Ø (76 mm)		
	CO-200-R,4	\$881.00	1
	Watts - 4"Ø (102 mm)		

Note: Spec 22 1423 - 2

Backwater Valve	BV-200 Watts - cast iron body, no-hub outlet, bronze seat and flapper		1
	BV-203 Watts - 3" (76 mm) pipe size	\$2,037.00	1
	BV-204 Watts - 4" (102 mm) pipe size	\$2,505.00	1
	BV-206 Watts - 6" (152 mm) pipe size	\$3,597.00	1
Note: Spec 22 1423 - 2			
Downspout Boot	RD-970 Watts - epoxy coated, 4" x 3" x 18", cast iron, countersunk securing strap, 4" no hub pipe connection	\$824.00	1
	RD-980 Watts - epoxy coated, 5" x 4" x 24", cast iron, countersunk securing strap, 4" no hub pipe connection	\$1,314.00	1
Note: Spec 22 1423 - 2. <i>Note: Quoting as suggestion.</i>			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
HB-2	SC8-4 Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)	\$81.25	1
Note: P-301 - Plumbing Fixture Schedule. <i>THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID</i>			
BFP (P11)	957-OSY : 2 1/2 Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 2-1/2"Ø (64 mm) pipe connection (0111584)	\$4,205.00	1
	957-AG Watts - 957-AG Air Gap (0111764)	\$269.50	1
	LF777SI : 2 1/2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2-1/2"Ø (64 mm) valve (0379117)	\$979.00	1
Note: P-301 - Keyed Plumbing Notes. <i>Note: Quoting as suggestion.</i>			
BFP (1" make up)	LF009M2-QT : 1 Watts - quarter turn ball-valves, 1"Ø (25 mm) pipe connection (0391004)	\$708.50	1
	909-AGC Watts - 909-AGC Air Gap (0881376)	\$106.50	1
	LF777SI : 1 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1"Ø (25 mm) valve (0379113)	\$105.00	1
Note: M-304 - Chilled & Hot Water Flow Diagram. <i>Note: Quoting as suggestion.</i>			

Section Brand: Delany

Label	Product No. Description	List Price	Qty.
WC-1/WC-2	U1802-1.6-SC-T42 Delany - EXPOSED TRUESENSE FLUSH VALVE for WATER CLOSET, SENSOR OPERATED, 9V HARDWIRED SYSTEM w/ ELECTRONIC NON-HOLD OPEN OVERRIDE BUTTON, 1.5" X 9" FLUSH CONNECTION w/ TOP SPUD, SLIPFIT CONNECTION TAILPIECE & SWEAT ADAPTOR KIT (1.6 GPF)	\$609.50	1
	2324-1 Delany - HARDWIRED TRANSFORMER for USE for 1 FLUSH VALVE for TRUESENSE	\$58.70	1
	2324-3 Delany - HARDWIRED TRANSFORMER & 3-WAY SPLITTER for USE w/ upto 3 FLUSH VALVES for TRUESENSE	\$79.00	1
Note: P-301 - Plumbing Fixture Schedule; Equal to Sloan Royal 110 ESS 1.6			
UR-1/UR-2	U1851-1-SC-T42 Delany - EXPOSED TRUESENSE VALVE for URINALS, SENSOR OPERATED, 9V HARDWIRED SYSTEM w/ NON-HOLD OPEN OVERRIDE BUTTON, 0.75" X 9" FLUSH CONNECTION w/ TOP SPUD, SLIPFIT CONNECTION TAILPIECE & SWEAT ADAPTOR KIT (1.0 GPF)	\$593.30	1
	2324-1 Delany - HARDWIRED TRANSFORMER for USE for 1 FLUSH VALVE for TRUESENSE	\$58.70	1
	2324-3 Delany - HARDWIRED TRANSFORMER & 3-WAY SPLITTER for USE w/ upto 3 FLUSH VALVES for TRUESENSE	\$79.00	1
Note: P-301 - Plumbing Fixture Schedule; Equal to Sloan Royal 186 ESS 1.0			

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
Mixing Valve	LFLM495-1 Powers - 1/2 LFLM495-1	\$312.00	1
Note: P-301 - WH-1 Water Heater Piping Diagram. <i>Note: Quoting as suggestion, no model number specified.</i>			

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

Terms

Above prices are net.
 All taxes are extra.
 Partial or expedited shipments, at customer request, may result in additional freight charges.
 Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.
 Please ensure that all quoted product meets your projects specifications.
 Our company will only be responsible for products shown on the attached quotation.