



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United States **Fax:** (513) 487-5337

Quotation:
Q-4250-S

To:	Contractor Holder Indiana Cincinnati, Ohio	Bid Date:	2018-12-14
Attn.:	N/A	Expiry Date:	2019-01-13
Phone:	800-542-1682	Creator:	Dave Evans , davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Rick Bayne , rickb@disney-mclane.com
		Shipping Address:	1815 E MORGAN ST, Kokomo, Indiana, United States

Job Name: Ivy Tech - Kokoma Campus

Engineer: IMEG Corp/KJWW **Architect:** American Structurepoint Inc

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
WHA	LF15M2-DR Series Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		1
	LF15M2-A-DR Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$175.00	1
	LF15M2-B-DR Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$336.00	1
	LF15M2-C-DR Watts - 33-60, fixture units, 1" (25 mm) connection	\$529.50	1
	LF15M2-D-DR Watts - 61-113 fixture units, 1" (25 mm) connection	\$1,118.00	1
	LF15M2-E-DR Watts - 114-154 fixture units, 1" (25 mm) connection	\$1,390.50	1
	LF15M2-F-DR Watts - 155-330 fixture units, 1" (25 mm) connection	\$1,656.00	1
Note: Dwg P800 Water Hammer Arrestor Schedule;			
Water Hammer Arrestor	SS Series Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		1
	SS-A Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$549.50	1
	SS-B Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$1,119.00	1
	SS-C Watts - 33-60, fixture units, 1" (25 mm) connection	\$1,672.00	1
	SS-D Watts - 61-113 fixture units, 1" (25 mm) connection	\$4,191.00	1
	SS-E Watts - 114-154 fixture units, 1" (25 mm) connection	\$4,731.50	1

	SS-F		\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection			
Note: Spec 22 1119 - 3				
WH-1	HY-725-88			1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp			
	HY-725-88,-6,-8		\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick			
	HY-725-88,-10,-12,-14		\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick			
	HY-725-88,-16,-18		\$1,829.50	1
	Watts - 16" (406 mm), 18" (457 mm) thick			
	HY-725-88,-20,-22,-24		\$1,870.00	1
	Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick			
Note: Spec 22 1119 - 4/5				
CO Floor	CO-200-R			1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top			
	CO-200-R,2		\$625.50	1
	Watts - 2"Ø (51 mm)			
	CO-200-R,3		\$661.00	1
	Watts - 3"Ø (76 mm)			
	CO-200-R,4		\$881.00	1
	Watts - 4"Ø (102 mm)			
Note: Spec 22 1319 - 1/2				
CO Floor	CO-260			1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top			
	CO-260,3,4,6,8		\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size			
Note: Spec 22 1319 - 1/2				
CO Wall	CO-380-RD			1
	Watts - cast iron body counter sunk, brass plug, round, stainless steel access cover and stainless steel vandal proof screw			
	CO-380-RD,2		\$232.00	1
	Watts - 2"Ø (51 mm)			
	CO-380-RD,3		\$286.00	1
	Watts - 3"Ø (76 mm)			
	CO-380-RD,4		\$343.50	1
	Watts - 4"Ø (102 mm)			
	CO-380-RD,6		\$727.00	1
	Watts - 6"Ø (152 mm)			
Note: Spec 22 1319 - 2				
CO Exterior	CO-200-RX-4			1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top			
	CO-200-RX-4,2		\$420.50	1
	Watts - 2"Ø (51 mm)			

	CO-200-RX-4,3	\$487.50	1
	Watts - 3"Ø (76 mm)		
	CO-200-RX-4,4	\$596.50	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 2			
FD-1	FS-730-1-F		1
	Watts - cast iron body, 6-1/4" (159 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, nickel bronze top, flange with weepholes		
	FS-730-1-F,2,3,4	\$3,253.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
Note: Spec 22 1319 - 3; Equal to Smith 3140			
FD-2	FD-230-A5		1
	Watts - cast iron floor drain/cleanout combination, side outlet, adjustable, cleanout top, removable cleanout plug, 5" (127 mm) diameter, nickel bronze, round strainer		
	FD-230-A5,2,3,4	\$1,416.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
Note: Spec 22 1319 - 3; Equal to Smith 2040			
WC-1/WC-2	ISCA-101-L/R	\$1,587.50	1
	Watts - single, horizontal, cast iron fitting, left/right side outlet		
	ISCA-101-D	\$2,967.00	1
	Watts - double, horizontal, epoxy coated, cast iron fitting, 4" no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, cast iron, foot support		
	ISCA-121	\$1,801.00	1
	Watts - single, vertical, cast iron fitting		
	ISCA-121-D	\$3,181.50	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection, 2" no hub vent connection. Epoxy coated cast iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support, adjustable for standard and wheelchair height, plated hardware and chrome nuts		
	ISCA-131-L/R	\$2,105.50	1
	Watts - single, vertical, cast iron fitting, left/right side outlet		
	ISCA-131-D	\$3,479.50	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"no hub waste connection and 4" no hub side inlet, 2" no hub vent connection. Epoxy coated cast iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, cast iron, foot support		
Note: Spec 22 4000 - 4/5			
<i>Note: Quoted carriers are rated for 500 lbs. If higher weight rating is required, please contact Disney McLane for revised selections and pricing.</i>			
UR-1/UR-2	CA-321	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
Note: Spec 22 4000 - 6			
EWC-1	CA-431-1	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
Note: Spec 22 4000 - 10			

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
TXA-1	DETA 42 Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 22 gallons (0212030)	\$2,824.00	1
<i>Note: Dwg P800 Thermal Expansion Absorber Schedule; Note: Quoted as per listed Volume and Acceptance.</i>			
BFP-1/BFP-2	LF909M1-QT : 2 Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391012)	\$3,363.00	1
	909-AGF Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	LF777SI : 2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
<i>Note: Dwg P800 Backflow Preventer Schedule;</i>			
BFP-1/BFP-2 Option	LF009M2-QT : 2 Watts - quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)	\$1,548.00	1
	909-AGF Watts - 909-AGF Air Gap (0881378)	\$208.00	1
	LF777SI : 2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
<i>Note: Dwg P800 Backflow Preventer Schedule;</i>			
BFP-3	LF909-QT : 3/4 Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, quarter turn ball-valves, 3/4"Ø (19 mm) pipe connection (0391008)	\$1,464.00	1
	909-AGC Watts - 909-AGC Air Gap (0881376)	\$106.50	1
	LF777SI : 3/4 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 3/4"Ø (19 mm) valve (0379112)	\$91.50	1
<i>Note: Dwg P800 Backflow Preventer Schedule;</i>			
BFP-3 Option	LF009M3-QT : 3/4 Watts - quarter turn ball-valves, 3/4"Ø (19 mm) pipe connection (0391003)	\$600.50	1
	909-AGA Watts - 909-AGA Air Gap (0881399)	\$92.50	1
	LF777SI : 3/4 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 3/4"Ø (19 mm) valve (0379112)	\$91.50	1
<i>Note: Dwg P800 Backflow Preventer Schedule;</i>			
H0se Bib	SC8-4 Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)	\$81.25	1

Note: Spec 22 1119 - 5

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
-------	----------------------------	------------	------

ETMV-1	ETV200AE050 Powers - HydroGuard XP Emergency Tempering Valve with Cold Water Bypass, Rough Bronze, Bottom/Top,T/P Gauge on Inlets	\$2,336.00	1
--------	---	------------	---

Note: Dwg P800 Thermostatic Mixing Valve Schedule & Spec 22 1119 - 4;

TMV-1	LFMM431HLAEMO Powers - HydroGuard XP Thermostatic Series LFMM430,0.5-65 gpm, SPLY FIX, Rough bronze,bottom/top,exposed, no cabinet	\$6,628.00	1
-------	--	------------	---

Note: Dwg P800 Thermostatic Mixing Valve Schedule;

Note: Quoting as suggestion, model number incomplete.

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.