



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337
 States

Quotation:
Q-4372-S

To:	Contractor Holder Indiana Cincinnati, Ohio	Bid Date:	2019-01-08
Attn.:	N/A	Expiry Date:	2019-02-07
Phone:	800-542-1682	Creator:	Dave Evans , davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Rick Bayne , rickb@disney-mclane.com
		Shipping Address:	4200 S. 18th Street, 47909, Lafayette, Indiana, United States

Job Name: Public Library (South Branch) - Lafayette, IN

Architect: KJG Architecture Inc

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
LA-2	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
Note: P5-100: Plumbing Fixture Schedule			
WC-1/WC-2	ISCA-102-L/R Watts - horizontal, cast iron fitting, 4"Ø, no hub waste connection, left/right side outlet, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, epoxy coated, ductile iron, foot support		1
	ISCA-102-D Watts - double, horizontal, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, epoxy coated, ductile iron, foot support	\$8,950.00	1
	ISCA-122 Watts - single, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, , 2"Ø, no hub vent connection. epoxy coated ductile iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, ductile iron foot support	\$5,108.00	1
	ISCA-122-D Watts - double, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection, , 2"Ø, no hub vent connection. epoxy coated ductile iron patent pending compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, ductile iron foot support	\$9,847.00	1

	ISCA-132-L/R	\$5,413.50	1
	Watts - single, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection and 4" Ø no hub side inlets, left/right side outlet, 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, ductile iron foot support		
	ISCA-132-D	\$10,146.00	1
	Watts - double, vertical, epoxy coated, cast iron fitting, 4"Ø, no hub waste connection and 4" Ø no hub side inlets, , 2"Ø, no hub vent connection. epoxy coated ductile iron patented compression seal faceplate assembly, adjustable ABS slide nipple with integral test cap, neoprene bowl gasket, epoxy coated, ductile iron foot support		
Note: P5-100: Plumbing Fixture Schedule			
UR-1/UR-2	CA-321	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
Note: P5-100: Plumbing Fixture Schedule			
EWC	CA-431-1	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
Note: P5-100: Plumbing Fixture Schedule			
NFHB	HY-725-88		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		
	HY-725-88,-6,-8	\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	HY-725-88,-10,-12,-14	\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-725-88,-16,-18	\$1,829.50	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	HY-725-88,-20,-22,-24	\$1,870.00	1
	Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick		
Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: Woodford B67			
FD-1	FD-100-M5-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" x 5" (127 mm x 127 mm) nickel bronze, square strainer, trap primer connection		
	FD-100-M5-7,2,3,4	\$643.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-M5-7,6	\$763.00	1
	Watts - 6"Ø (152 mm)		
Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: FD2290-ST			
FD-2	FD-100-A5-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 5" (127 mm) diameter, nickel bronze, round strainer, trap primer connection		
	FD-100-A5-7,2,3,4	\$481.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-A5-7,6	\$601.50	1
	Watts - 6"Ø (152 mm)		
Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: FD2290			
TP-1/TP-2	LFTP300-DR Series		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		

	LFTP300T	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	LFTP300S	\$270.00	1
	ATS - 1/2", Solder Inlet and Threaded Outlet Connect		
	LFTP300-DU-DR	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: PPP PR-500, Please be advised, Electronic Trap Primer not Available			
WHA BELLOWS	SS Series		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: P5-100: Plumbing Fixture Schedule;			
WHA PISTON	LF15M2-DR Series		1
	Watts - pre-charged copper water hammer arrestor with polypropylene piston, EPDM o-ring seal and brass NPT threaded connection. Designed to operate on all domestic and commercial lines up to 150psi (10.6 bar) working pressure. Temperature range from 33°F to 180°F (0.5°C to 82°C)		
	LF15M2-A-DR	\$175.00	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	LF15M2-B-DR	\$336.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	LF15M2-C-DR	\$529.50	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	LF15M2-D-DR	\$1,118.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	LF15M2-E-DR	\$1,390.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	LF15M2-F-DR	\$1,656.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
Note: P5-100: Plumbing Fixture Schedule;			
FCO	CO-200-R		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200-R,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-R,3	\$661.00	1
	Watts - 3"Ø (76 mm)		

	CO-200-R,4	\$881.00	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 15 0150 - 2; CARPET CLAMPING FLANGE (-CF) = \$285.00 LIST ADDER CARPET MARKER (-RC) = \$78.00 LIST ADDER NB HEAVY DUTY (-RX) = \$155.00 LIST ADDER TILE RECESS (-T) = NO ADDITIONAL TERRAZZO RECESS (-U) = \$354.00 LIST ADDER		
ECO	CO-200-RX-4-6-13		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top, vandal proof, all galvanized		
	CO-200-RX-4-6-13,2	\$795.00	1
	Watts - 2" (51mm)		
	CO-200-RX-4-6-13,3	\$862.00	1
	Watts - 3" (76mm)		
	CO-200-RX-4-6-13,4	\$971.00	1
	Watts - 4" (102mm)		
	Note: Spec 15 0150 - 3;		
WCO	CO-460-RD		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$364.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$417.50	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$611.50	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 15 0150 - 3;		
UNFINISHED CO	CO-460		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		
	CO-460,2	\$228.00	1
	Watts - 2"Ø (51 mm)		
	CO-460,3	\$284.00	1
	Watts - 3"Ø (76 mm)		
	CO-460,4	\$441.00	1
	Watts - 4"Ø (102 mm)		
	Note: Spec 15 0150 - 3;		

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
ET-1	ETX-60 Watts - Pressurized Expansion Tanks for Heating and Cooling System, painted exterior, steel tank, rugged flexible butyl, diaphragm, free standing, 12 psi pre-charge pressure, 220°F maximum temperature, tank volume of 33 gallons (0066611)	\$488.50	1
	Note: M6-002: Expansion Tank Schedule; Quoting Model as an Alternate Suggestion.		
ET-2	ETX-30 Watts - Pressurized Expansion Tanks for Heating and Cooling System, painted exterior, steel tank, rugged flexible butyl, diaphragm, mounts to supply piping, 12 psi pre-charge pressure, 220°F maximum temperature, tank volume of 4.5 gallons (0066606)	\$85.75	1
	Note: M6-002: Expansion Tank Schedule; Quoting Model as an Alternate Suggestion.		

T&P RELIEF VALVE	LF100XL -4 Watts - ASME Self-Closing T&P Relief Valve	\$39.00	1
	LF100XL -8 Watts - ASME Self-Closing T&P Relief Valve	\$35.00	1
Note: M6-002: Boiler Schedule			
RPZ	957-OSY : 2 1/2 Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 2-1/2"Ø (64 mm) pipe connection (0111584)	\$4,205.00	1
	957-AG Watts - 957-AG Air Gap (0111764)	\$269.50	1
	77F-DI-125 : 2 1/2 Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 2-1/2"Ø (64 mm) valve (0825201)	\$264.50	1
Note: P1-100: Sheet Keynotes			
FIRE BFP	LF757DCDA-OSY-CFM : 6 Watts - 304 schedule 40 stainless steel housing and sleeve with groove end connections, reversible elastomer discs, UL/FM outside stem & yoke gate valve, flange connections, cubic feet per minute reading, 6"Ø (152 mm) pipe connection (0122712)	\$7,498.00	1
Note: P5-100: Fire Sprinkler Riser Detail			

Section Brand: Pure Water

Label	Product No. Description	List Price	Qty.
WS	M4047B-29NT Watts Pure Water - 120K 2" Water Simplex, Water Softener w/ 18x40 Brine Tank; Flow Rated: 35gpm @ 15psi> to 55gpm @25psi >	\$6,174.44	1
	I5044 Watts Pure Water - Vacuum Breaker	\$63.49	1
Note: P5-100: Plumbing Fixture Schedule; Quoting Water Softener based on Specified Model Number; EQUAL TO: Culligan HCE-120-2			

Section Brand: Delany

Label	Product No. Description	List Price	Qty.
LA-1/LA-2	SF1596-B w/ DP4 Delany - INFINITE SERIES - CURVED DESIGN - ELECTRONIC LAVATORY FAUCET for COLD or PREMIXED WATER. POWERED by EXTERNALLY MOUNTED 9V BATTERY	\$560.00	1
Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: Sloan ETF-610-4-B-BDT			
WC-1/WC-2	U1802-1.6-TMO Delany - EXPOSED TRUESENSE FLUSH VALVE for WATER CLOSET, SENSOR OPERATED, 9V HARDWIRED SYSTEM w/ ELECTRONIC NON-HOLD OPEN OVERRIDE BUTTON, 1.5" X 9" FLUSH CONNECTION w/ TOP SPUD, SLIPFIT CONNECTION TAILPIECE, SWEAT ADAPTOR KIT & TRUE MECHANICAL OVERRIDE BUTTON (1.6 GPF)	\$640.70	1
	2324-1 Delany - HARDWIRED TRANSFORMER for USE for 1 FLUSH VALVE for TRUESENSE	\$58.70	1
	2324-3 Delany - HARDWIRED TRANSFORMER & 3-WAY SPLITTER for USE w/ upto 3 FLUSH VALVES for TRUESENSE	\$79.00	1

Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: Sloan 111 ES-S TMO

UR-1/UR-2	U1851-1-SC-T42	\$593.30	1
Delany - EXPOSED TRUESENSE VALVE for URINALS, SENSOR OPERATED, 9V HARDWIRED SYSTEM w/ NON-HOLD OPEN OVERRIDE BUTTON, 0.75" X 9" FLUSH CONNECTION w/ TOP SPUD, SLIPFIT CONNECTION TAILPIECE & SWEAT ADAPTOR KIT (1.0 GPF)			
	2324-1	\$58.70	1
Delany - HARDWIRED TRANSFORMER for USE for 1 FLUSH VALVE for TRUESENSE			
	2324-3	\$79.00	1
Delany - HARDWIRED TRANSFORMER & 3-WAY SPLITTER for USE w/ upto 3 FLUSH VALVES for TRUESENSE			

Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: Sloan 186-1 ES-S TMO DFB, w/ EL-154

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
LA-1/LA-2	LFE480-10	\$284.00	1
Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish			

Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: Sloan BDT

TMV	LFMM431-10	\$1,290.00	1
Powers - HydroGuard XP Thermostatic Series LFMM430			

Note: P5-100: Plumbing Fixture Schedule; EQUAL TO: Lawler 61-25 (72907-10)

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings.

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.