



**Address:** 7737 Reinhold Drive, **Phone:** (513) 861-1682  
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337  
 States

**Quotation:**  
**Q-4373-S**

<b>To:</b>	<b>Contractor Holder Indiana</b> Cincinnati, Ohio	<b>Bid Date:</b>	2019-01-09
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2019-02-08
<b>Phone:</b>	800-542-1682	<b>Creator:</b>	Dave Evans, davee@disney-mclane.com
<b>Fax:</b>	877-476-1682	<b>Sales Rep.:</b>	Rick Bayne, rickb@disney-mclane.com
		<b>Shipping Address:</b>	209 West Brinton Street Cicero, Indiana, United States

**Job Name: Hamilton North Public Library - Cicero,IN**

**Engineer:** CMTA Inc Prospect **Architect:** Peterson Architecture

**Comments:**

**Section Brand: Watts Drainage**

Label	Product No. Description	List Price	Qty.
Access Panel	<b>CO-300-S-S9</b> Watts - scoriated, square, access cover, nickel bronze, concealed mounting flanges, 9" (229 mm) square	\$887.00	1
<i>Note: Spec 22 01 00-2; Equal to Zurn Z1460</i>			
ECO	<b>CO-200-RX-4</b> Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top		1
	<b>CO-200-RX-4,2</b> Watts - 2"Ø (51 mm)	\$420.50	1
	<b>CO-200-RX-4,3</b> Watts - 3"Ø (76 mm)	\$487.50	1
	<b>CO-200-RX-4,4</b> Watts - 4"Ø (102 mm)	\$596.50	1
<i>Note: Spec 22 01 00-2; Equal to Zurn Z1400</i>			
CO Exposed	<b>CO-380</b> Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		1
	<b>CO-380,2</b> Watts - 2"Ø (51 mm)	\$96.25	1
	<b>CO-380,3</b> Watts - 3"Ø (76 mm)	\$148.50	1
	<b>CO-380,4</b> Watts - 4"Ø (102 mm)	\$205.50	1
	<b>CO-380,6</b> Watts - 6"Ø (152 mm)	\$420.50	1
<i>Note: Spec 22 01 00-3; Equal to Zurn Z1440</i>			
CO Exposed	<b>CO-460</b> Watts - cast iron stack, no-hub outlet, counter sunk brass plug		1
	<b>CO-460,2</b> Watts - 2"Ø (51 mm)	\$228.00	1
	<b>CO-460,3</b> Watts - 3"Ø (76 mm)	\$284.00	1

	<b>CO-460,4</b>		\$441.00	1
	Watts - 4"Ø (102 mm)			
<b>Note:</b> Spec 22 01 00-3; Equal to Zurn Z1445				
CO Concealed	<b>CO-460-RD</b>			1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw			
	<b>CO-460-RD,2</b>		\$364.00	1
	Watts - 2"Ø (51 mm)			
	<b>CO-460-RD,3</b>		\$417.50	1
	Watts - 3"Ø (76 mm)			
	<b>CO-460-RD,4</b>		\$611.50	1
	Watts - 4"Ø (102 mm)			
<b>Note:</b> Spec 22 01 00-3; Equal to Zurn Z1445-1				
CO Finished Concrete/Masonry Tile	<b>CO-200-S</b>			1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" x 5" (127 mm x 127 mm) square, nickel bronze top			
	<b>CO-200-S,2</b>		\$625.50	1
	Watts - 2"Ø (51 mm)			
	<b>CO-200-S,3</b>		\$661.00	1
	Watts - 3"Ø (76 mm)			
	<b>CO-200-S,4</b>		\$881.00	1
	Watts - 4"Ø (102 mm)			
<b>Note:</b> Spec 22 01 00-3; Equal to Zurn Z1400-T				
CO VCT/Linoleum	<b>CO-200-TS</b>			1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" x 5" (127 mm x 127 mm) square, nickel bronze top with tile recess			
	<b>CO-200-TS,2</b>		\$625.50	1
	Watts - 2"Ø (51 mm)			
	<b>CO-200-TS,3</b>		\$661.00	1
	Watts - 3"Ø (76 mm)			
	<b>CO-200-TS,4</b>		\$881.00	1
	Watts - 4"Ø (102 mm)			
<b>Note:</b> Spec 22 01 00-3; Equal to Zurn Z1400-Tx				
CO Poured Floors	<b>CO-200-U</b>			1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top with terrazzo recess			
	<b>CO-200-U,2</b>		\$978.00	1
	Watts - 2"Ø (51 mm)			
	<b>CO-200-U,3</b>		\$1,014.00	1
	Watts - 3"Ø (76 mm)			
	<b>CO-200-U,4</b>		\$1,235.00	1
	Watts - 4"Ø (102 mm)			
<b>Note:</b> Spec 22 01 00-3; Equal to Zurn Z1400-Z				
FD-1	<b>FD-100-A6-7</b>			1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" (152 mm) diameter, nickel bronze, round strainer, trap primer connection			
	<b>FD-100-A6-7,2,3,4</b>		\$589.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size			

	<b>FD-100-A6-7,6</b>	\$709.00	1
	Watts - 6"Ø (152 mm)		
	<b>Note: Spec 22 01 00-3; Equal to Zurn ZN415B</b>		
FD-2	<b>FD-320-Y-1-5-7</b>		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 8" (203 mm) diameter, nickel bronze, round grate, sediment bucket, trap primer tapping		
	<b>FD-320-Y-1-5-7,2,3,4</b>	\$1,186.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>FD-320-Y-1-5-7,6</b>	\$1,306.00	1
	Watts - 6"Ø (152 mm)		
	<b>Note: Spec 22 01 00-3; Equal to Zurn ZN511</b>		
FPWH	<b>HY-725</b>		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door		
	<b>HY-725,-6,-8</b>	\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	<b>HY-725,-10,-12,-14</b>	\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	<b>HY-725,-16,-18</b>	\$1,830.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	<b>HY-725,-20,-22,-24</b>	\$1,870.00	1
	Watts - 20" (508 mm), 22" (559 mm), 24" (610 mm) thick		
	<b>Note: Spec 22 01 00-4; Equal to Zurn Z1320</b>		
WHA	<b>SS Series</b>		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	<b>SS-A</b>	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	<b>SS-B</b>	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	<b>SS-C</b>	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	<b>SS-D</b>	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	<b>SS-E</b>	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	<b>SS-F</b>	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
	<b>Note: Spec 22 01 00-5; Equal to Zurn Z1700</b>		
P-2	<b>CA-321</b>	\$839.00	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.		
	<b>Note: Spec 22 02 00-3;</b>		
P-3	<b>TCA-411 Series</b>		1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		

	<b>TCA-411</b>	\$989.50	1
	Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>TCA-411-D</b>	\$1,411.00	1
	Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		
	<b>Note:</b> Spec 22 02 00-3;		
P-6	<b>CA-431-1</b>	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
	<b>Note:</b> Spec 22 02 00-4		

### Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
Expansion Tank	<b>PLT-12</b> Watts - Potable Water Expansion Tanks, drawn steel construction, rugged flexible butyl, diaphragm, 20 psi pre-charge pressure, 150 psi maximum pressure, 200°F maximum temperature, tank volume of 4.5 gallons (0067371)	\$129.00	1
	<b>Note:</b> Dwg P1.0 Dometic Hot Water Piping Schematic		
HB	<b>SC8-4</b> Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)	\$81.25	1
	<b>Note:</b> Spec 22 01 00-4; Equal to Woodford 24		

### Section Brand: Powers

Label	Product No. Description	List Price	Qty.
TMV	<b>LFSH1434-13</b> Powers - HydroGuard Hi/Lo Master Tempering Valve - 127 gpm, Rough brass, Standard, T/P Gauge on outlet, Rough Brass	\$5,574.00	1
	<b>Note:</b> Dwg P1.0 Dometic Hot Water Piping Schematic; Equal to Bradley 559-3080		
P-3	<b>LFE480-10</b> Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish	\$284.00	1
	<b>Note:</b> Spec 22 02 00-3; Equal to Zurn ZW3870		

### Section Brand: Delany

Label	Product No. Description	List Price	Qty.
P-1/P-1A	<b>U402-1.6-SM</b> Delany - EXPOSED FLUSHBOY ULTRA VALVE for HIGH EFFICIENCY WATER CLOSET w/SIDEARM (Side Mounted Sensor Actuator), 1.5" x 9" FLUSH CONNECTION, TOPSPUD, SWEAT ADAPTOR KIT & SLIPFIT CONNECTION (1.6 GPF)	\$508.30	1
	<b>Note:</b> Spec 22 02 00-3; Equal to Zurn ZER6000-CP-WS1		
P-2	<b>U451-1-SM</b> Delany - EXPOSED FLUSHBOY ULTRA VALVE for URINAL w/ 0.75" x 9" FLUSH CONNECTION, TOP SPUD, SWEAT ADAPTOR KIT, & SLIPFIT TAILPIECE (1.0 GPF)	\$474.25	1
	<b>Note:</b> Spec 22 02 00-3; Equal to Zurn ZER6003-CP-WS1		

**Special Terms:**

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.