



Address: 7737 Reinhold Drive, **Phone:** (513) 861-1682
 Cincinnati, Ohio, 45237 United **Fax:** (513) 487-5337
 States

Quotation:
Q-4383-S

To:	Contractor Holder Indiana Cincinnati, Ohio	Bid Date:	2019-01-10
Attn.:	N/A	Expiry Date:	2019-02-09
Phone:	800-542-1682	Creator:	Dave Evans , davee@disney-mclane.com
Fax:	877-476-1682	Sales Rep.:	Rick Bayne , rickb@disney-mclane.com
		Shipping Address:	Cabela Drive and Indianapolis Boulevard , Hammond, Indiana, United States

Job Name: Medistar Micro Hospital

Engineer: SWAssociates Consulting Engineers, Inc. **Architect:** Kaim Associates, Inc

Comments:

Section Brand: Watts Drainage

Label	Product No. Description	List Price	Qty.
GT-1	GI-75-K Watts - steel, epoxy coated, skid-proof cover, secured with hex head center bolts, integral stainless steel flow control plate, double wall, deep seal trap, no-hub connections, flow rate of 75 GPM	\$23,993.00	1
<i>Note: P200 - Underfloor Plan - Plumbing & P801 - Detail 3; Equal to JR Smith 8450E Extension Up to 12" = \$5,290.00 Extension over 12", add per inch = \$451.00</i>			
FD/FD-2	FD-340-Y-7 Watts - 12-1/2" (318 mm) diameter cast iron body no-hub outlet, 12-1/2" (318 mm) diameter, ductile iron, round grate, trap primer connection		1
	FD-340-Y-7,2,3,4,5,6,8 Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm), 5"Ø (127 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size	\$1,194.00	1
<i>Note: P201 - Keyed Notes #6 & P701 - Plumbing Fixture Schedule & Spec 22 1319 - 4; Equal to JR Smith 2131 Note: Trap Seal by others.</i>			
FD	FS-730 Watts - cast iron body, 6-1/4" (159 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, porcelain enamel coated cast iron grate		1
	FS-730,4 Watts - 4"Ø (102 mm) outlet size	\$2,116.00	1
<i>Note: P201 - Keyed Notes #13; Equal to JR Smith 3420. Note: Quoting no hub outlet. Note: Trap Seal by others.</i>			
L-1/L-2/L-3	TCA-411 Series Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	TCA-411 Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	TCA-411-D Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1

Note: P701 - Plumbing Fixture Schedule

CSS-1	ISCA-560 Series	\$1,430.00	1
	Watts - floor mounted, cast iron fitting, no hub waste connection, no hub vent connection (specify size). Cast iron compression seal faceplate assembly with steel mounting brackets, adjustable ABS nipple with integral test cap, heavy gauge, steel, offset uprights with welded feet		
	Note: P701 - Plumbing Fixture Schedule		
EWC-1	CA-431-1	\$1,214.50	1
	Watts - floor mounted bi-level carrier, heavy gauge steel uprights with integral welded feet, universal steel hanger support plate, plated hardware.		
	Note: P701 - Plumbing Fixture Schedule		
SH-1 (floor drain)	FD-100P-A5-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body push-on outlet, 5" (127 mm) diameter nickel bronze, adjustable round strainer, trap primer connection		
	FD-100P-A5-7,2,3,4	\$481.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100P-A5-7,6	\$601.00	1
	Watts - 6"Ø (152 mm)		
	Note: P701 - Plumbing Fixture Schedule & Spec 22 1319 - 4; Equal to JR Smtih 2005L		
TP-2	LFTP300-DR Series		1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap		
	LFTP300T	\$270.00	1
	Watts - 1/2", Threaded Inlet and Outlet Connect		
	LFTP300S	\$270.00	1
	Watts - 1/2", Solder Inlet and Threaded Outlet Connect		
	LFTP300-DU-DR	\$189.00	1
	Watts - lead free brass with EPDM seal, pressure drop activated, integral air gap, distribution unit		
	Note: P701 - Plumbing Fixture Schedule & Spec 22 1119 - 11; Equal to Precision Plumbing Products PR-500		
FD-1	FD-100-A6-6-7		1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" (152 mm) diameter nickel bronze, adjustable round strainer, vandal proof, trap primer connection		
	FD-100-A6-6-7,2,3,4	\$643.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	FD-100-A6-6-7,6	\$763.00	1
	Watts - 6"Ø (152 mm)		
	Note: P701 - Plumbing Fixture Schedule & Spec 22 1319 - 4; Equal to Zurn ZN415B		
FS-1	FS-730-FC-1-6-150		1
	Watts - cast iron body, 6-1/4" (159 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, nickel bronze top, flange w/weepholes & flashing clamp,Vandal Proof (-1,-3 Only),1/2 Grate		
	FS-730-FC-1-6-150,2,3,4	\$3,523.00	1
	Watts - 2" (51 mm), 3" (76 mm), 4" (102 mm) outlet size		
	Note: P701 - Plumbing Fixture Schedule; Equal to Zurn ZN1900		
FCO	CO-200-R		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	CO-200-R,2	\$625.50	1
	Watts - 2"Ø (51 mm)		
	CO-200-R,3	\$661.00	1
	Watts - 3"Ø (76 mm)		

	CO-200-R,4	\$881.00	1
	Watts - 4"Ø (102 mm)		
	Note: P701 - Plumbing Fixture Schedule; Equal to Zurn ZN1400		
	CARPET CLAMPING FLANGE (-CF) = \$285.00 LIST ADDER		
	CARPET MARKER (-RC) = \$78.00 LIST ADDER		
	NB HEAVY DUTY (-RX) = \$155.00 LIST ADDER		
	TILE RECESS (-T) = NO ADDITIONAL		
	TERRAZZO RECESS (-U) = \$354.00 LIST ADDER		
FCO	CO-260		1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top		
	CO-260,3,4,6,8	\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		
	Note: P701 - Plumbing Fixture Schedule		
WCO-1	CO-590-RD		1
	Watts - threaded brass cleanout plug with countersunk head, stainless steel access cover and vandal proof stainless steel screw		
	CO-590-RD,1.5	\$184.00	1
	Watts - 1-1/2"Ø (39 mm)		
	CO-590-RD,2	\$188.00	1
	Watts - 2"Ø (51 mm)		
	CO-590-RD,3	\$232.00	1
	Watts - 3"Ø (76 mm)		
	CO-590-RD,4	\$307.50	1
	Watts - 4"Ø (102 mm)		
	CO-590-RD,5	\$429.00	1
	Watts - 5"Ø (126 mm)		
	CO-590-RD,6	\$661.00	1
	Watts - 6"Ø (152 mm)		
	Note: P701 - Plumbing Fixture Schedule; Equal to ZS1468		
WH-1	HY-725		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door		
	HY-725,-6,-8	\$1,547.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	HY-725,-10,-12,-14	\$1,690.00	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		
	HY-725,-16,-18	\$1,830.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	Note: P701 - Plumbing Fixture Schedule; Equal to Zurn Z1300		
WH-2	HY-700		1
	Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze, dual-temp, all bronze head, wall mount, concealed, polished bronze hydrant face, integral vacuum breaker, nickel bronze box and door, galvanized casing, 8-1/2" x 6-1/2" (165 mm)		
	HY-700,-6,-8	\$3,868.00	1
	Watts - 6" (152 mm), 8" (203 mm) thick		
	HY-700,-10,-12,-14	\$4,093.50	1
	Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick		

	HY-700,-16,-18	\$4,323.00	1
	Watts - 16" (406 mm), 18" (457 mm) thick		
	Note: P701 - Plumbing Fixture Schedule		
	<i>THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID</i>		
NFRH	HY-900	\$3,160.00	1
	Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, roof hydrant with and lift handle and lock option, integral epoxy coated cast iron roof mounting plate with clamping collar, 1/8" NPT drain port		
	Note: P701 - Plumbing Fixture Schedule; Equal to JR Smith 5906		
WHA	SS Series		1
	Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		
	SS-A	\$549.50	1
	Watts - 1-11 fixture units, 1/2" (13 mm) connection		
	SS-B	\$1,119.00	1
	Watts - 12-32 fixture units, 3/4" (19 mm) connection		
	SS-C	\$1,672.00	1
	Watts - 33-60, fixture units, 1" (25 mm) connection		
	SS-D	\$4,191.00	1
	Watts - 61-113 fixture units, 1" (25 mm) connection		
	SS-E	\$4,731.50	1
	Watts - 114-154 fixture units, 1" (25 mm) connection		
	SS-F	\$5,815.00	1
	Watts - 155-330 fixture units, 1" (25 mm) connection		
	Note: P702 - Water Hammer Absorber Schedule & Spec 22 1119 - 10; Equal to Josam 75000 Series		
Wall Cleanout	CO-460-RD		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug, round, stainless steel access cover and stainless steel vandal proof screw		
	CO-460-RD,2	\$364.00	1
	Watts - 2"Ø (51 mm)		
	CO-460-RD,3	\$417.50	1
	Watts - 3"Ø (76 mm)		
	CO-460-RD,4	\$611.50	1
	Watts - 4"Ø (102 mm)		
	Note: P801 - Detail 1 & Spec 22 1319 - 3 & Spec 22 1423 - 3		
	<i>Note: Quoting as per detail.</i>		
Backwater Valve	BV-200		1
	Watts - cast iron body, no-hub outlet, bronze seat and flapper		
	BV-203	\$2,037.00	1
	Watts - 3" (76 mm) pipe size		
	BV-204	\$2,505.00	1
	Watts - 4" (102 mm) pipe size		
	BV-206	\$3,597.00	1
	Watts - 6" (152 mm) pipe size		
	Note: Spec 22 1319 - 3 & Spec 22 1423 - 2		
	<i>Note: Quoting as suggestion.</i>		
Exposed cleanout	CO-460		1
	Watts - cast iron stack, no-hub outlet, counter sunk brass plug		

	CO-460,2	\$228.00	1
	Watts - 2"Ø (51 mm)		
	CO-460,3	\$284.00	1
	Watts - 3"Ø (76 mm)		
	CO-460,4	\$441.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 3 & Spec 22 1423 - 2			
<i>Note: Quoting as suggestion.</i>			
Floor	CO-200X-RX		1
Cleanout	Watts - 7" (178 mm) diameter, cast iron body inside caulk outlet, brass plug, 5" (127 mm) round, heavy duty, nickel bronze top		
	CO-200X-RX,2	\$778.05	1
	Watts - 2"Ø (51 mm)		
	CO-200X-RX,3	\$815.50	1
	Watts - 3"Ø (76 mm)		
	CO-200X-RX,4	\$1,035.50	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 3 & Spec 22 1423 - 3			
Trench	DX-RSS	\$1,628.00	1
Drain	Watts - UV stabilized talc-filled polypropylene channels with 6" (152 mm) no-hub bottom or end outlet(s), pre-sloped trench, 12" (305 mm) wide, including frame connectors, grate lockdowns and construction covers, ductile iron frame, framed anchored grate, reinforced stainless steel slotted, Class E		
Note: Spec 22 1319 - 5 & Spec 22 1423 - 4			
<i>Please note trench drain price is per foot.</i>			
<i>Note: Quoting as suggestion, no model specified.</i>			
THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID			
Trench	FG-GV	\$65.75	1
Drain	Watts - Frame Guard, Galvanized Steel Frame Guard (option)		
Note: Spec 22 1319 - 5 & Spec 22 1423 - 4			
<i>Please note trench drain price is per foot.</i>			
THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID			
Expansion	RD-900		1
Joints	Watts - neoprene expansion joint, no hub (MJ) clamps		
	RD-900,2	\$298.00	1
	Watts - 2"Ø (51 mm)		
	RD-900,3	\$345.50	1
	Watts - 3"Ø (76 mm)		
	RD-900,4	\$404.00	1
	Watts - 4"Ø (102 mm)		
Note: Spec 22 1319 - 5 & Spec 22 1423 - 5			
THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID			
Catch	CB-624-DI	\$1,344.00	1
Basin	Watts - UV stabilized talc-filled polypropylene channels with integral 4" (102 mm) and 6" (152 mm) no hub bottom outlets, 6" (152 mm) wide, 24" (610 mm) long, ductile iron grate, Class F		
Note: Spec 22 1423 - 4.			
<i>Note: Quoting as suggestion, no model specified.</i>			

Downspout	RD-980	\$1,314.00	1
Boots	Watts - epoxy coated, 5" x 4" x 24", cast iron, countersunk securing strap, 4" no hub pipe connection		
Note: Spec 22 1423 - 5.			
<i>Note: Quoting as suggestion.</i>			
Downspout	RD-940		1
Nozzle	Watts - cast nickel bronze, anchor flange and pre-drilled counter-sunk mounting holes		
	RD-940,2,3,4	\$1,083.00	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	RD-940,5,6	\$1,942.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	RD-940,8	\$2,654.50	1
	Watts - 8"Ø (203 mm)		
	RD-940,10	\$3,464.00	1
	Watts - 10"Ø (254 mm)		
	RD-940,12	\$4,289.00	1
	Watts - 12"Ø (305 mm)		

Note: Spec 22 1423 - 5.

Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
BFP (3/4")	LF009M3-QT : 3/4 Watts - quarter turn ball-valves, 3/4"Ø (19 mm) pipe connection (0391003)	\$673.00	1
	909-AGA Watts - 909-AGA Air Gap (0881399)	\$92.50	1
	LF777SI : 3/4 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 3/4"Ø (19 mm) valve (0379112)	\$91.50	1
Note: P201 - Keyed Notes #7,#9			
BFP (1 1/2")	LF009M2-QT : 1 1/2 Watts - quarter turn ball-valves, 1-1/2"Ø (38 mm) pipe connection (0391006)	\$1,304.00	1
	909-AGC Watts - 909-AGC Air Gap (0881376)	\$106.50	1
	LF777SI : 1 1/2 Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/2"Ø (38 mm) valve (0379115)	\$213.00	1
Note: P201 - Keyed Notes #11 & P803 - Detail 4			
Fire BFP	774DCDA-OSY-CFM : 4 Watts - thermoplastic construction with stainless steel hinge pins, cam arm and cam bearing, 300 series stainless steel body molded thermoplastic construction seats, resilient seated isolation valves, UL/FM outside stem & yoke gate valve, flange connections, cubic feet per minute reading, 4"Ø (102 mm) pipe connection (0438004)	\$6,610.00	1
Note: P201 - Keyed Notes #14 & P801 - Detail 8			
<i>Note: Tamper switches by others.</i>			
CM-1/IM-1 (coffee maker)	SD2-MF : 1/4 Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061651)	\$170.50	1

	SD2-MF : 3/8	\$180.50	1
	Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655)		
	Note: P201 - Keyed Notes #25 & P701 - Plumbing Fixture Schedule		
L-2 (mixing valve)	LFUSG-B M2	\$297.50	1
	Watts - valve shall control temperature from a low of 1/4gpm, 3/8"Ø (10 mm) male compression (0204143)		
	Note: P701 - Plumbing Fixture Schedule; Equal to American Standard 605XTMV		
	<i>Note: Mounting box by others.</i>		
ET	DETA 60	\$3,438.00	1
	Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 26 gallons (0212031)		
	Note: P702 - Expansion Tanks Schedule; Equal to Amtrol ST-60VC		
BFP (3")	LF909-LF : 3	\$5,969.00	1
	Watts - Lead Free cast copper silicon alloy body, replaceable seats, internal pressure differential relief valve in between check modules tight closing resilient seated shut-off valve, without shut-off valves, 3"Ø (76 mm) pipe connection (0792189)		
	909-AGF	\$208.00	1
	Watts - 909-AGF Air Gap (0881378)		
	77F-DI-FDA-125 : 3	\$680.50	1
	Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 3"Ø (76 mm) valve (0825211)		
	Note: P802 - Detail 11		
BFP (3" alternate)	957-OSY : 3	\$4,700.00	1
	Watts - 304 stainless steel, schedule 40 pipe with groove end connection sleeve accessible housing, replaceable elastomer discs differential pressure relief valve between and below the check modules, drip tight shut-off valves, UL/FM outside stem & yoke gate valve, flange connections, 3"Ø (76 mm) pipe connection (0111585)		
	957-AG	\$269.50	1
	Watts - 957-AG Air Gap (0111764)		
	77F-DI-FDA-125 : 3	\$680.50	1
	Watts - lead free cast iron body, graphite gasket, drain/blowoff connection furnished with closure plug, flange ends, ANSI B16.1 Class 125, 200 psi at 210°F WOG, non-shock, 3"Ø (76 mm) valve (0825211)		
	Note: P802 - Detail 11		
Pressure Reducing Valve	LF223 : 1 1/2	\$3,070.00	1
	Watts - high capacity water pressure reducing valves,1-1/2" (38 mm) connection with lead-free brass body construction,EPDM valve disc,enlarged diaphragm, spring cage and seat orifice for super capacity,reinforced Buna-N diaphragm,adjustable reduced pressure range: 25 to 75psi (172 to 517 kPa),temperature range: 33°F - 160°F (0.5°C - 71°C),maximum working pressure: 300psi (20.7 bar),standard reduced pressure setting: 50psi (345 kPa). (0298568)		
	Note: P803 - Detail 4.		
	<i>Note: Quoting as suggestion.</i>		
Hose Bibb	SC8-3	\$81.25	1
	Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, no kink faucet, 1/2" copper sweat connection with vacuum breaker (0611350)		

	SC8-4	\$81.25	1
	Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)		
	Note: Spec 22 1119 - 8. Note: Quoting as suggestion.		
BFP (1/2")	LF009-QT : 1/2	\$505.50	1
	Watts - quarter turn ball-valves, 1/2"Ø (13 mm) pipe connection (0391002)		
	909-AGA	\$92.50	1
	Watts - 909-AGA Air Gap (0881399)		
	LF777SI : 1/2	\$68.25	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1/2"Ø (13 mm) valve (0379111)		
	Note: Spec 22 4300 - 11.		

Section Brand: Delany

Label	Product No. Description	List Price	Qty.
WC-1	S402-1.28 Delany - EXPOSED SABER VALVE for WATER CLOSET w/ SLIPFIT CONNECTION, 1.5" x 9" FLUSH CONNECTION, TOP SPUD, MASHAERATOR BYPASS & SWEAT ADAPTOR KIT (1.28 GPF)}	\$183.00	1
	Note: P701 - Plumbing Fixture Schedule; Equal to Sloan Royal 111-1.28		
WC-2	F461-1.28 Delany - EXPOSED FLUSHBOY VALVE for WATER CLOSET w/ BEDPAN DIVERTER (#977}, GROUND JOINT & OFFSET FLUSH CONNECTION for 1.5" TOP SPUD (1.28 GPF}	\$538.80	1
	Note: P701 - Plumbing Fixture Schedule THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID		
CSS-1	F418 Delany - EXPOSED FLUSHBOY VALVE, CLINICAL SERVICE SINK (4.5 GPF}	\$188.80	1
	Note: P701 - Plumbing Fixture Schedule; Equal to Sloan Royal 117H Note: Quoting 4.5 GPF in lieu of 6.5 GPF.		

Section Brand: Powers

Label	Product No. Description	List Price	Qty.
EW-1 (mixing valve)	ES150AEQ000 Powers - HydroGuard XP Series, Emergency Tempering Valve Supply Fixture with Cold Water Bypass, Bottom/Top, 8.7 gpm, Rough Bronze, Stainless Steel, Wall Mounted	\$2,557.00	1
	Note: P701 - Plumbing Fixture Schedule & Spec 22 4500 - 4; Equal to Guardian G3600LF Note: Cabinet finish not specified, quoting stainless steel as suggestion.		
SH-1	F7270003YW Powers - VisuGuard LCD T/P Shower Valve, Fahrenheit, Deluxe, Metal Hose, 30" Glide Rail, Diverter, Concealed, 1/2" IPS, Metal Handle, in-line Vacuum Breaker	\$1,588.00	1
	Note: P701 - Plumbing Fixture Schedule. Note: Quoting as per model number (without shower head). THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID		
SH-1 (w/ shower head)	F727H102YW Powers - VisuGuard LCD T/P Shower Valve, Fahrenheit, Low Flow (1.5 gpm), Chrome-Plated, Standard Arm & Flange, 36" Chrome ADA Wall Grab Bar System, Diverter, Concealed, 1/2" IPS, Metal Handle, in-line Vacuum Breaker	\$1,641.00	1
	Note: P701 - Plumbing Fixture Schedule. Note: Quoting as per description (with shower head). THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID		

SH-2	E427EK1070W	\$1,630.00	1
Powers - HydroGuard Thermostatic Valve, Concealed Valve, Angled, with Strainer, 1/2" IPS, Standard, Chrome-Plated Brass, Standard Arm and Flange, Professional, Vinyl Hose, 24" Glide Rail, Vacuum Breaker,in-Line			
Note: P701 - Plumbing Fixture Schedule. THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID			
ES/EW-1	ETV400AEQ000	\$4,725.00	1
Powers - HydroGuard XP Emergency Tempering Valve with Cold Water Bypass, Rough Bronze, Bottom/Top, Stainless Steel, Wall Mounted			
Note: P701 - Plumbing Fixture Schedule & Spec 22 4500 - 4; Equal to Leonad TM-800-LF Note: Cabinet finish not specified, quoting stainless steel as suggestion.			
TMV-1	LFIS200F00LP	\$26,586.00	1
Powers - IntelliStation, Digital Water Tempering and Recirculating System, 2"(50mm)Inlets, 2 1/2"(63mm), 2" Return Pipe, Less Pump			
Note: P702 - Thermostatic Mixing Valve Schedule; Equal to Armstrong DVR50RBS			

Section Brand: MAPA Products

Label	Product No. Description	List Price	Qty.
Roof	MPH-24FP:24/9	\$983.75	1
Hydrant	MAPA Products - Pedestal Hydrant,Under-deck flange,e Stainless Steel Shroud and Base,Supply connection is made at the 3/4" fitting on the reservoir at the base of the Hydrant		

Note: P802 - Detail 10

Special Terms:

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

Terms

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.