



**Address:** 7737 Reinhold Drive, **Phone:** (513) 861-1682  
 Cincinnati, Ohio, 45237 United States **Fax:** (513) 487-5337

**Quotation:**  
**Q-4387-S**

<b>To:</b>	<b>Contractor Holder Ohio</b> Cincinnati, Ohio	<b>Bid Date:</b>	2019-01-10
<b>Attn.:</b>	N/A	<b>Expiry Date:</b>	2019-02-09
<b>Phone:</b>	800-542-1682	<b>Creator:</b>	Dave Evans , davee@disney-mclane.com
<b>Fax:</b>	877-476-1682	<b>Sales Rep.:</b>	Jason Plageman , jasonp@disney-mclane.com
		<b>Shipping Address:</b>	2324 Rohr Rd, (6023 Alum Creek Drive), Columbus, Ohio, United States

**Job Name: Loves Travel Stop - Obetz OH**

**Engineer:** MTF Engineering Inc. **Architect:** Pascal Aughtry & Associates, Llc

**Comments:**

**Section Brand: Watts Drainage**

Label	Product No. Description	List Price	Qty.
SK-1/HS-1	<b>TCA-411 Series</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.		1
	<b>TCA-411</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, steel cross plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$989.50	1
	<b>TCA-411-D</b> Watts - back-to-back floor mounted carrier, heavy gauge steel offset uprights with welded feet, double cross steel plate with integral mounting bracket, sliding adjustable arm brackets and adjustable cast iron concealed arms with mounting clips, leveling screws and basin locking device.	\$1,411.00	1
<b>Note: FSP4.1 - Plumbing Fixture Schedule &amp; HAP4.1 - Plumbing Fixture Schedule</b>			
RH-1	<b>HY-900</b> Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, roof hydrant with and lift handle and lock option, integral epoxy coated cast iron roof mounting plate with clamping collar, 1/8" NPT drain port	\$3,160.00	1
<b>Note: FSP4.1 - Plumbing Fixture Schedule &amp; HAP4.1 - Plumbing Fixture Schedule &amp; P4.1 - Plumbing Fixture Schedule</b> <b>THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID</b>			
UR-1/UR-2	<b>CA-321</b> Watts - floor mounted carrier, heavy gauge steel offset uprights with welded feet, universal steel hanger support plate and bottom bearing plate with integral mounting bracket, plated hardware.	\$839.00	1
<b>Note: P4.1 - Plumbing Fixture Schedule</b>			
YH-1/YH-2	<b>HY-800</b> Watts - 3/4" (19 mm) diameter hose connection, combination 3/4" female of 1" male threaded inlet connection, non-freeze, epoxy coated heavy duty cast iron head, bronze internal working parts and valve housing with 1" galvanized steel casing, yard hydrant with and lift handle and lock option, 1/8" NPT drain port		1
	<b>HY-800-1</b> Watts - 1' (305 mm) depth	\$1,100.00	1
	<b>HY-800-2</b> Watts - 2' (610 mm) depth	\$1,161.00	1

	<b>HY-800-3</b>	\$1,223.00	1
	Watts - 3' (914 mm) depth		
	<b>HY-800-4</b>	\$1,290.00	1
	Watts - 4' (1219 mm) depth		
	<b>HY-800-5</b>	\$1,349.00	1
	Watts - 5' (1524 mm) depth		
	<b>HY-800-6</b>	\$1,411.00	1
	Watts - 6' (1829 mm) depth		

**Note:** P4.1 - Plumbing Fixture Schedule & Spec 22 1006 - 4.

*THIS PRODUCT IS BEING OFFERED AS A VOLUNTARY SUBSTITUTION AND MUST BE LISTED AS SUCH AT THE TIME OF THE BID*

RD-1	<b>RD-300-D-F-L-K</b>		1
	Watts - 16-5/8" (422 mm) diameter cast iron body, flashing clamp, no-hub outlet, 15-1/4" (387mm) diameter, underdeck clamp, adjustable extension flange, vandal proof dome, ductile iron dome		
	<b>RD-300-D-F-L-K,2,3,4</b>	\$1,941.50	1
	Watts - 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-300-D-F-L-K,5,6</b>	\$2,244.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	<b>RD-300-D-F-L-K,8,10</b>	\$2,546.50	1
	Watts - 8"Ø (203 mm), 10"Ø (254 mm) outlet size		

**Note:** Spec 22 1006 - 2

RD-2	<b>RD-250-L</b>		1
	Watts - 19-1/2" x 10-3/4" (495 mm x 273 mm) rectangular, one-piece cast iron combination roof drain with deck flange, flashing clamps with integral gravel guard, 2-1/2" (64 mm) overflow standpipe, no-hub outlet, 8" (203 mm) diameter, polyethylene dome, Vandal Proof		
	<b>RD-250-L,2,3,4</b>	\$845.50	1
	Watts - 2" (51 mm), 3" (76 mm), 4" (102 mm) outlet size		

**Note:** Spec 22 1006 - 2

Downspout	<b>RD-940-83</b>		1
Nozzles	Watts - cast nickel bronze, anchor flange and pre-drilled counter-sunk mounting holes, no hub, stainless steel bird screen		
	<b>RD-940-83,3,4</b>	\$1,633.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm) outlet size		
	<b>RD-940-83,5,6</b>	\$2,165.00	1
	Watts - 5"Ø (127 mm), 6"Ø (152 mm) outlet size		
	<b>RD-940-83,8</b>	\$3,204.00	1
	Watts - 8"Ø (203 mm)		

**Note:** Spec 22 1006 - 2

SD-1	<b>FD-1102-M6</b>	\$834.00	1
	Watts - 8-1/8" (206 mm) diameter cast iron body no-hub outlet, 6" (152 mm) square, stainless steel, square strainer, 2"Ø (51 mm), 3"Ø (76 mm), 4"Ø (102 mm) outlet sizes		

**Note:** Spec 22 1006 - 3; Equal to JR Smith 2005

FS-1	<b>FS-740-FC-1-150</b>		1
	Watts - cast iron body, 8-1/4" (209 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, nickel bronze top, Flange w/ Weepholes & Flashing Clamp, 1/2" Grate		
	<b>FS-740-FC-1-150,2,3,4</b>	\$3,558.00	1
	Watts - 2" (51mm), 3" (76mm), 4" (102mm) outlet size		

**Note:** Spec 22 1006 - 3

FS-2	<b>FS-740-FC-1-150</b>		1
	Watts - cast iron body, 8-1/4" (209 mm) deep, no-hub outlet, aluminum dome bottom strainer, 9" x 9" (229 mm x 229 mm) square, nickel bronze top, Flange w/ Weepholes & Flashing Clamp, 1/2" Grate		
	<b>FS-740-FC-1-150,2,3,4</b>	\$3,558.00	1
	Watts - 2" (51mm), 3" (76mm), 4" (102mm) outlet size		
<b>Note: Spec 22 1006 - 3</b>			
CO-1	<b>CO-300-MF</b>	\$1,391.00	1
	Watts - epoxy coated, 11" (279 mm) diameter, cast iron body, 8" (203 mm) round, extra heavy duty, ductile iron top		
	<b>CO-380</b>		1
	Watts - 6" (152 mm) diameter, cast iron body no-hub outlet, removable counter sunk brass plug		
	<b>CO-380,2</b>	\$96.25	1
	Watts - 2"Ø (51 mm)		
	<b>CO-380,3</b>	\$148.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-380,4</b>	\$205.50	1
	Watts - 4"Ø (102 mm)		
	<b>CO-380,6</b>	\$420.50	1
	Watts - 6"Ø (152 mm)		
<b>Note: Spec 22 1006 - 3; Equal to JR Smith 4250</b>			
CO-2	<b>CO-200-RX-4</b>		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, heavy duty, ductile iron top		
	<b>CO-200-RX-4,2</b>	\$420.50	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200-RX-4,3</b>	\$487.50	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200-RX-4,4</b>	\$596.50	1
	Watts - 4"Ø (102 mm)		
<b>Note: Spec 22 1006 - 3; Equal to JR Smith 4221</b>			
CO-3	<b>CO-200-R</b>		1
	Watts - 7" (178 mm) diameter, cast iron body no-hub outlet, brass plug, 5" (127 mm) round, nickel bronze top		
	<b>CO-200-R,2</b>	\$625.50	1
	Watts - 2"Ø (51 mm)		
	<b>CO-200-R,3</b>	\$661.00	1
	Watts - 3"Ø (76 mm)		
	<b>CO-200-R,4</b>	\$881.00	1
	Watts - 4"Ø (102 mm)		
<b>Note: Spec 22 1006 - 3; Equal to JR Smith 4140</b>			
CO-3	<b>CO-260</b>		1
	Watts - 10-3/16" (259 mm) diameter, cast iron body no-hub outlet, brass plug, 8" (203 mm) round, heavy duty ductile iron top		
	<b>CO-260,3,4,6,8</b>	\$1,210.00	1
	Watts - 3"Ø (76 mm), 4"Ø (102 mm), 6"Ø (152 mm), 8"Ø (203 mm) outlet size		
<b>Note: Spec 22 1006 - 3</b>			
CO-4	<b>CO-380-RD</b>		1
	Watts - cast iron body counter sunk, brass plug, round, stainless steel access cover and stainless steel vandal proof screw		

	<b>CO-380-RD,2</b> Watts - 2"Ø (51 mm)	\$232.00	1
	<b>CO-380-RD,3</b> Watts - 3"Ø (76 mm)	\$286.00	1
	<b>CO-380-RD,4</b> Watts - 4"Ø (102 mm)	\$343.50	1
	<b>CO-380-RD,6</b> Watts - 6"Ø (152 mm)	\$727.00	1

**Note:** Spec 22 1006 - 3; Equal to JR Smith 4422

WH-1	<b>HY-725-88</b> Watts - 3/4" (19 mm) diameter hose connection, 3/4" (19 mm) female x 1" (25 mm) male pipe connection, non-freeze hydrant, all bronze head, wall mount, concealed, bronze wall casing, chrome plated face, integral vacuum breaker, nickel bronze box and door, wall clamp		1
	<b>HY-725-88,-6,-8</b> Watts - 6" (152 mm), 8" (203 mm) thick	\$1,547.00	1
	<b>HY-725-88,-10,-12,-14</b> Watts - 10" (254 mm), 12" (305 mm), 14" (356 mm) thick	\$1,690.00	1
	<b>HY-725-88,-16,-18</b> Watts - 16" (406 mm), 18" (457 mm) thick	\$1,829.50	1

**Note:** Spec 22 1006 - 4; Equal to Woodford B67

WHA	<b>SS Series</b> Watts - pre-charged, all stainless steel shock arrestors with stainless steel bellows, and male IPS threaded connection. Designed to operate on all domestic and commercial lines up to 150 psi working pressure. Temperature range from -100°F to 300°F (-73°C to 149°C)		1
	<b>SS-A</b> Watts - 1-11 fixture units, 1/2" (13 mm) connection	\$549.50	1
	<b>SS-B</b> Watts - 12-32 fixture units, 3/4" (19 mm) connection	\$1,119.00	1
	<b>SS-C</b> Watts - 33-60, fixture units, 1" (25 mm) connection	\$1,672.00	1
	<b>SS-D</b> Watts - 61-113 fixture units, 1" (25 mm) connection	\$4,191.00	1
	<b>SS-E</b> Watts - 114-154 fixture units, 1" (25 mm) connection	\$4,731.50	1
	<b>SS-F</b> Watts - 155-330 fixture units, 1" (25 mm) connection	\$5,815.00	1

**Note:** Spec 22 1006 - 5

### Section Brand: Watts Regulators

Label	Product No. Description	List Price	Qty.
Dual Check BFP	<b>SD3-MF : 1/4</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061653)	\$391.50	1
	<b>SD3-MF : 3/8</b> Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061657)	\$391.50	1

**Note:** FSP1.2 - Sheet Keynotes & HAP1.2 - Sheet Keynotes & P1.2 - Sheet Keynotes

Mixing Valve	<b>LFMMVM1-US : 1/2</b> Watts - Lead Free cast copper silicon alloy body, solid wax hydraulic principle thermostat, integral filter washers and check valves, ASSE 1069, ASSE 1070, ASSE 1017, cUPC AND IAPMO listed, valve shall control temperature from a low of 1/2gpm, 5gpm at 10psi and 8gpm at 20psi drop across the valve, 1/2"Ø valve, union solder (0559115)	\$314.00	1
<b>Note:</b> FSP1.2 - Sheet Keynotes & HAP1.2 - Sheet Keynotes & P4.1 - Plumbing Fixture Schedule & Spec 22 1006 - 6			
Expansion Tank	<b>DETA 5</b> Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 3.5 gallons (0212026)	\$1,832.00	1
<b>Note:</b> FSP4.1 - Water Heater Schedule			
BFP	<b>SS009M3-QT : 3/4</b> Watts - investment cast 316 stainless steel assembly body, replaceable seats and silicone seat discs, internal pressure differential relief valve in between check modules 316 stainless steel, ball valve shut-offs with PTFE seat blow out proof 304 stainless steel stem and 304 stainless steel tee handles, quarter turn ball-valves, 3/4"Ø (19 mm) pipe connection (0062968)	\$3,029.00	1
	<b>LF777SI : 3/4</b> Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 3/4"Ø (19 mm) valve (0379112)	\$91.50	1
<b>Note:</b> HAP1.2 - Sheet Keynotes & Domestic Water Plan & P1.2 - Sheet Keynotes <i>Note: Size of backflow not specified, quoting as suggestion as per drawing.</i>			
Expansion Tank	<b>DETA 12</b> Watts - carbon steel shell, FDA approved butyl, bladder, 40 psi pre-charge pressure, tank volume of 5 gallons (0212027)	\$2,109.00	1
<b>Note:</b> HAP4.1 - Water Heater Schedule & P4.1 - Water Heater Schedule			
DCDA	<b>757DCDA-OSY-CFM : 8</b> Watts - Double Check Detector Assembly, UL/FM Outside stem and yoke resilient seated gate valves, 8"(200mm)	\$11,251.00	1
<b>Note:</b> P1.0 - Detail 2. <i>Note: Quoting as suggestion.</i>			
BFP (2" house protection)	<b>LF919-QT : 2</b> Watts - Lead Free cast copper silicon alloy body, corrosion resistant plastic guide, replaceable seat and seat discs pressure differential relief valve located in the zone between check valves, push-in type with internal sensing line and bronze cover, resilient seated isolation valves, quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0065376)	\$1,626.00	1
	<b>919AGF</b> Watts - Air Gaps, Elbows and Test Cocks for Reduced Pressure Zone Assemblies, 4-1/2" (111mm) x 8-1/2"(216mm)(0881577)	\$208.00	1
	<b>LF777SI : 2</b> Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)	\$314.00	1
<b>Note:</b> P1.2 - Sheet Keynotes			
BFP (2" house protection - alternate)	<b>LF009M2-QT : 2</b> Watts - quarter turn ball-valves, 2"Ø (51 mm) pipe connection (0391007)	\$1,548.00	1
	<b>909-AGF</b> Watts - 909-AGF Air Gap (0881378)	\$208.00	1

	<b>LF777SI : 2</b>	\$314.00	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 2"Ø (51 mm) valve (0379116)		
<b>Note: P1.2 - Sheet Keynotes</b>			
BFP (1 1/4" fuel island)	<b>LF919-QT : 1 1/4</b>	\$1,309.00	1
	Watts - Lead Free cast copper silicon alloy body, corrosion resistant plastic guide, replaceable seat and seat discs pressure differential relief valve located in the zone between check valves, push-in type with internal sensing line and bronze cover, resilient seated isolation valves, quarter turn ball-valves, 1-1/4"Ø (32 mm) pipe connection (0065374)		
	<b>919AGF</b>	\$208.00	1
	Watts - Air Gaps, Elbows and Test Cocks for Reduced Pressure Zone Assemblies, 4-1/2" (111mm) x 8-1/2"(216mm)(0881577)		
	<b>LF777SI : 1 1/4</b>	\$150.50	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/4"Ø (32 mm) valve (0379114)		
<b>Note: P1.2 - Sheet Keynotes</b>			
BFP (1 1/4" fuel island - alternate)	<b>LF009M2-QT : 1 1/4</b>	\$1,247.00	1
	Watts - quarter turn ball-valves, 1-1/4"Ø (32 mm) pipe connection (0391005)		
	<b>909-AGA</b>	\$92.50	1
	Watts - 909-AGA Air Gap (0881399)		
	<b>LF777SI : 1 1/4</b>	\$150.50	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/4"Ø (32 mm) valve (0379114)		
<b>Note: P1.2 - Sheet Keynotes</b>			
BFP (limited area protection)	<b>LF009M2-QT : 1 1/2</b>	\$1,304.00	1
	Watts - quarter turn ball-valves, 1-1/2"Ø (38 mm) pipe connection (0391006)		
	<b>909-AGC</b>	\$106.50	1
	Watts - 909-AGC Air Gap (0881376)		
	<b>LF777SI : 1 1/2</b>	\$213.00	1
	Watts - lead free cast copper silicon alloy body, #20 mesh, 304 stainless steel screen, lead free copper silicon alloy retainer cap tapped for closure plug, NBR gasket, lead free brass plug, 1-1/2"Ø (38 mm) valve (0379115)		
<b>Note: P1.2 - Sheet Keynotes</b>			
<i>Note: Quoting quarter turn valves in lieu of OSY. Specified OSY valves not available in 1.5"</i>			
HB-1	<b>SC8-4</b>	\$81.25	1
	Watts - adjustable packing nut, cast brass body, wall mount, Watts Model 8B tamper-proof vacuum breaker with break-away screw, lawn faucet, 3/4" female NPT regular pattern with cast iron hand wheel (0611450)		
<b>Note: Spec 22 1006 - 3; Equal to Woodford 24</b>			
<i>Note: Quoting brass finish in lieu of chrome.</i>			
ASSE 1032 BFP	<b>SD2-MF : 1/4</b>	\$170.50	1
	Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 1/4"Ø (6 mm) pipe connection (0061651)		

**SD2-MF : 3/8**

\$180.50 1

Watts - 316 stainless steel body with FDA approved internal rubber components, recommended on post-mix carbonated beverage equipment and dispensing equipment for tea and coffee. certified to ANSI / NSF Standard 18, manual food and beverage dispensing equipment, male flare connection, 3/8"Ø (10 mm) pipe connection (0061655)

*Note: Spec 22 1006 - 5***Section Brand: Watts ProLine**

Label	Product No. Description	List Price	Qty.
FD-1	<b>FD12-6R-2PVC</b> Watts - On-Grade PVC/ABS Adjustable Floor Drain w/Round Strainer, 2""(51mm) PVC and 6"" (152mm) Round NB	\$115.00	1

*Note: Spec 22 1006 - 2*

FD-2	<b>FD12-6R-3PVC-GNB</b> Watts - On-Grade PVC/ABS Adjustable Floor Drain w/Round Strainer 3" PVC, 6" Round Nickel Bronze Funnel, Nickel Bronze Round Funnel	\$206.00	1
------	---	----------	---

*Note: Spec 22 1006 - 3*

FD-3	<b>FD12-6R-4PVC-HNB</b> Watts - On-Grade PVC/ABS Adjustable Floor Drain w/Round Strainer 4" PVC, 6" Round Nickel Bronze Funnel, Nickel Bronze Oval Funnel	\$240.00	1
------	--	----------	---

*Note: Spec 22 1006 - 3***Section Brand: Fiat**

Label	Product No. Description	List Price	Qty.
MSK-1	<b>MSB2424</b> FIAT - MOP SERVICE BASIN 24"	\$373.00	1
	<b>832AA</b> FIAT - MSB HOSE AND BRACKET	\$40.00	1
	<b>1239BB24</b> FIAT - 24" ALUM BUMPER GUARD	\$80.00	1
	<b>889CC</b> FIAT - MSB MOP HANGER BRACKET	\$84.00	1
	<b>MSG2424</b> FIAT - 24" X 24" WALL GUARDS	\$289.00	1
	<b>QDC3XH</b> FIAT - 3" QUICK DRAIN CONNECTOR	\$20.00	1

*Note: FSP4.1 - Plumbing Fixture Schedule & HAP4.1 - Plumbing Fixture Schedule & P4.1 - Plumbing Fixture Schedule.***Section Brand: Powers**

Label	Product No. Description	List Price	Qty.
L-1/L-2/L-3 (mixing valve)	<b>LFE480-10</b> Powers - Lavatory Tempering Valve, 0.50 gpm minimum flow, 3/8" Compression Rough Bronze Finish	\$284.00	1

*Note: P4.1 - Plumbing Fixture Schedule & Spec 22 1006 -6; Equal to Zurn ZW3870XLT*

**Section Brand: Delany**

Label	Product No. Description	List Price	Qty.
WC-1	<b>E402-1.6-SC</b> Delany - EXPOSED EMPIRE VALVE for WATER CLOSET, PISTON OPERATED w/ 1.5" x 9" FLUSH CONNECTION, TOP SPUD & SLIPFIT TAILPIECE (1.6 GPF)}	\$165.30	1

**Note:** P4.1 - Plumbing Fixture Schedule; Equal to Toto TMT1NNC

**Section Brand: Armstrong**

Label	Product No. Description	List Price	Qty.
RCP-1	<b>Astro 225BS 3/4" SWT</b> Armstrong - ASTRO 2 3-Speed Circulator, Lead Free Sweat Connection, 3/4"	\$349.00	1
Recirc Pump	<b>Astro 230SS</b> Armstrong - ASTRO 2 3-Speed Circulator, Stainless Steel Body Construction, Includes Check Valve, Flanged	\$347.00	1

**Note:** FSP4.1 - Water Heater Schedule; Equal to Taco 006-B4

**Note:** HAP4.1 - Water Heater Schedule; Equal to Taco 008-BC6

**Special Terms:**

Due to the current unpredictable market climate, pricing on this quote is firm for 30 days after its creation. NOTE: This quotation is based on the interpretation of the specifications, plans/drawings, and addendums provided. Disney McLane & Associates will not be held responsible for variations with regards to pricing, quantities, changes, and/or approvals in products as a result of modifications or inaccuracies to specifications and/or plans/drawings

**Terms**

Above prices are net.

All taxes are extra.

Partial or expedited shipments, at customer request, may result in additional freight charges.

Any material over & above that what is listed is in addition to and therefore not provided for by this quotation.

Please ensure that all quoted product meets your projects specifications.

Our company will only be responsible for products shown on the attached quotation.